

# 64781 2000 W 240 V

Halogen (>  $130\ V$ ) Double End | Offering a broad portfolio of high quality double end halogen lamps used in the stage and studio markets



#### Areas of application

- Stage & Theatre
- Studio, TV, & Film
- Professional Photography
- Club & Disco

### Product features and benefits

- Robust construction for lasting performance
- Consistent color over the life of the lamps
- Instant on and nearly constant luminous flux over the life of the lamp
- Broad product portfolio supporting the stage and studio markets
- Dimmable with traditional amber shift





## Product datasheet

### Technical data

### **General Product Information**

ANSI code	-
LIF code	P2/27
Global order reference	64781


### **Electrical Data**

Nominal wattage	2000 W
Nominal voltage	240 V

### **Photometric Data**

Nominal luminous flux	50000 lm
Useful luminous flux (Фuse)	46670 lm
Φuse value refers to luminous flux	360
Color temperature	3200 K
Correlated color temperature CCT	3144 K
Chromaticity coordinate x	0.427
Chromaticity coordinate y	0.401
Color rendering index Ra	100

## **Physical Attributes & Dimensions**



Lamp base	RX7s
Diameter	30.0 mm
Diameter	30.0 mm
Length	138.1 mm
Length with base excl. base pins/connection	138.50 mm
Product weight	95.80 g

## Product datasheet

## **Operating Conditions**

Burning position	p15
Dimmable	Yes

### Lifetime Data

Nominal lifetime	300 hr
Troning tretime	300 111

### **Environmental & Regulatory Information**

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)			
Primary article identifier 4050300283500			
Declaration no. in SCIP database	No declarable substances contained		
Candidate list substance 1	t substance 1 No declarable substances contained		

### Product datasheet

#### Safety advice

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (protective shields, grids, etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. There must also be a warning sign to indicate that the lamps give off high levels of heat. Detailed information is available on request.

#### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300283500	64781 2000 W 240 V	Folding carton box 1	58 mm x 58 mm x 164 mm	0.55 dm <sup>3</sup>	119.00 g
4050300365763	64781 2000 W 240 V	Shipping carton box 12	320 mm x 260 mm x 250 mm	20.80 dm <sup>3</sup>	2000.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.