OSRAM

LEDinspect WIRE-FREE SLIM 600



Wire-Free charging compatible

Simply place on the Wire-Free charging pad to securely hold and recharge



Slim design

Easily place bright 600 Lumens white light where you need it most



Built to last

IK08 and IP54 rated to survive the rigors of the professional workshop



The easiest way to recharge inspection lights

Inspection lights are a vital part of any professional's toolbox. Removing the need to find and plug into the correct charging cable, OSRAM's wire-free inspection lights recharge without hassle by simply being placed on the magnetic charging pad. This innovative design not only enhances convenience but also supports an uninterrupted workflow.

Product datasheet

Technical data

Product information

Application (Category and Product specific)	LED inspection lights
---	-----------------------

General Product Information


Electrical Data


Nominal wattage	5 W
Nominal voltage	3.7 V

Photometric Data

Color temperature	5700 K
Nominal luminous flux	600 lm
Light color LED	White

Physical Attributes & Dimensions





Product weight	240.00 g
Length	325.0 mm
Width	43.0 mm
Height	37.0 mm

Lifetime Data

Guarantee	2 years
	,

Capabilities

Technology	LED

Product datasheet

Certificates & standards

Standards CE / EMC / MSDS / ROHS

Logistical data

Watt hour per battery	9.20
-----------------------	------

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)		
Candidate list substance 1	Lead	
CAS No. of substance 1	7439-92-1	
Safe use instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.	
Declaration no. in SCIP database	39eac002-3892-45bc-922c-294d6f9430fb	

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172393140	INSPECTION LAMP	Folding carton box 1	65 mm x 46 mm x 182 mm	0.54 dm ³	595.00 g
4062172393157	INSPECTION LAMP	Shipping carton box 6	160 mm x 150 mm x 210 mm	5.04 dm ³	6170.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

	File
乙	User instruction LEDinspect WIRE-FREE SLIM 600
大	User instruction GPRS_Safety symbols instructions

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaime

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

Product datasheet

OSRAM