

CorePro LED PLS 3.5W 840 2P G23

929003756702



CorePro, LED, PL-S, EM/Mains, 115 mm, 3.5 W, 7W PL-S, 4000 K, 390 lm, CRI 82, 30000 hour(s)



CorePro, LED, PL-S, EM/Mains, 115 mm, 3.5 W, LED alternative to 7W PL-S, 4000 K, 390 lm, CRI 82, 30000 hour(s), 111 lm/W, EEL E, G23, Beam angle 120 degree(s), Plastic, RG0, SDCM 6, PF 0.9, IP20, SVM 0.4, PstLM 1

General Information

Cap-Base	G23
Nominal lifetime	30,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
Flux measurement reference	Sphere
Warranty period	3 years

Light Technical

Color Code	840 [CCT of 4000K]
Beam Angle (Nom)	120 degree(s)
Luminous Flux	390 lm
Color Designation	Cool White (CW)
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	111 lm/W
Color Consistency	<6
Color rendering index (CRI)	82

LLMF At End Of Nominal Lifetime (Nom)	70 %
---------------------------------------	------

Photobiological safety according to EN 62471	RG0
--	-----

Operating and Electrical

Input Frequency	50 to 60 Hz
-----------------	-------------

Power Consumption	3.5 W
-------------------	-------

Lamp Current (Nom)	22 mA
--------------------	-------

Starting Time (Nom)	0.5 s
---------------------	-------

Warm-up time to 60% light	0.5 s
---------------------------	-------

Power Factor (Fraction)	0.9
-------------------------	-----

Voltage (Nom)	220-240 V
---------------	-----------

LED alternative to fluorescent lamp power	7W PL-S
---	---------

Inrush current at mains	6.6
-------------------------	-----

Max. lamp no. on MCB B type 10A - Mains	116
---	-----

Max. lamp no. on MCB B type 10A – EM ballast without Compensation Capacitor.	500
--	-----

Max. lamp no. on MCB B type 10A – EM ballast with Compensation Capacitor.	-
---	---

Max. lamp no. on MCB B type 16A - Mains	186
---	-----

Max. lamp no. on MCB B type 16A – EM ballast without Compensation Capacitor.	801
--	-----

Max. lamp no. on MCB B type 16A – EM ballast with Compensation Capacitor.	-
---	---

Ballast Compatibility	EM/Mains
-----------------------	----------

Temperature

T-Case Maximum (Nom)	45 °C
----------------------	-------

Controls and Dimming

Dimmable	No
----------	----

Mechanical and Housing

Bulb Finish	Frosted
-------------	---------

Bulb Material	Plastic
---------------	---------

Product Length	115 mm
----------------	--------

Bulb Shape	PL-S
------------	------

Net Weight (Piece)	0.038 kg
--------------------	----------

Approval and Application

Energy Efficiency Class	E
-------------------------	---

Energy Saving Product	Yes
-----------------------	-----

Approval Marks	RoHS compliance
----------------	-----------------

Energy Consumption kWh/1000 h	4 kWh
-------------------------------	-------

EPREL Registration Number	1820626
---------------------------	---------

CE mark	Yes
---------	-----

EU RoHS compliant	Yes
-------------------	-----

Flickering value (PstLM) - Flickering value as per EN 61000-3-3	1
---	---

Stroboscopic effect visibility measure (SVM)	0.4
--	-----

Ambient temperature range	-20 to +45 °C
---------------------------	---------------

Application Conditions

Wireless Technology	Not applicable
---------------------	----------------

Product Data

Order product name	CorePro LED PLS 3.5W 840 2P G23
--------------------	---------------------------------

Full product name	CorePro LED PLS 3.5W 840 2P G23
-------------------	---------------------------------

Full product code	872016928656600
-------------------	-----------------

Order code	929003756702
------------	--------------

Material Nr. (12NC)	929003756702
---------------------	--------------


Numerator - Quantity Per Pack	1
-------------------------------	---

EAN/UPC - Product/Case	8720169286566
------------------------	---------------

Numerator - Packs per outer box	20
---------------------------------	----



EAN/UPC - Case	8720169286573
----------------	---------------

Dimensional drawing




Product	D1	D	A1	A2	A3
CorePro LED PLS 3.5W 840 2P G23	16 mm	31 mm	79 mm	115 mm	137 mm

Photometric data




Spectral Power Distribution Colour - CorePro LED PLS 3.5W 840 2P G23

General uniform lighting - CorePro LED PLS 3.5W 840 2P G23




Light Distribution Diagram - CorePro LED PLS 3.5W 840 2P G23


Lifetime




FailureRate




Lumen Maintenance Diagram - CorePro LED PLS 3.5W 840 2P G23



LifetimeVsTc



Life Expectancy Diagram



Lumen Maintenance Diagram - CorePro LED PLS 3.5W 840 2P G23

Related Documents

Documents and certificates	Document Name	Download
Environmental Product Declaration	EPD-Philips-CorePro-LED-PLS-COMF-7149659-Ref-929003756902-EPD.pdf	Download
Installation Instructions	online-QIG-for-324166138011-Installation-INI.pdf	Download
Photometry and lighting design	Document Name	Download
IES File	CorePro-LED-PLS-840-2P-G23-9290037567-IES.IES	Download

