PHILIPS

CorePro LED PLC 360D 5.9W 3CCT 2P G24d

929004252802





CorePro, LED, PL-C, EM/Mains, 115 mm, 5.9 W, 13W PL-C, 3000 K, 4000 K, 6500 K, 810 lm, 850 lm, 850 lm, CRI 82, 30000 hour(s)

CorePro, LED, PL-C, EM/Mains, 115 mm, 5.9 W, LED alternative to 13W PL-C, 3000 K, 4000 K, 6500 K, 810 lm, 850 lm, 850 lm, CRI 82, 30000 hour(s), 144 lm/W, EEL D, G24d, Beam angle 360 degree(s), Plastic, RG1, SDCM 6, PF 0.9, IP20, SVM 0.4, PstLM 1

General Information

Cap-Base	G24d
Nominal lifetime	30,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
Flux measurement reference	Sphere
Warranty period	3 years

Light Technical

Color Code	3000/4000/6500
Beam Angle (Nom)	360 degree(s)
Luminous Flux	810 lm
Color Designation	3000/4000/6500
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	144 lm/W

Color Consistency	<6
Color rendering index (CRI)	82
LLMF At End Of Nominal Lifetime (Nom)	70 %
Photobiological safety according to EN 62471	RG1

Operating and Electrical

Input Frequency	50 to 60 Hz
Power Consumption	5.9 W
Lamp Current (Nom)	35 mA
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.9
Voltage (Nom)	220-240 V
LED alternative to fluorescent lamp power	13W PL-C
Inrush current at mains	5.2
Max. lamp no. on MCB B type 10A - Mains	45
Max. lamp no. on MCB B type 10A – EM ballast without Compensation Capacitor.	110
Max. lamp no. on MCB B type 10A – EM ballast with Compensation Capacitor.	-
Max. lamp no. on MCB B type 16A - Mains	55
Max. lamp no. on MCB B type 16A – EM ballast without Compensation Capacitor.	145
Max. lamp no. on MCB B type 16A – EM ballast with Compensation Capacitor.	-
Ballast Compatibility	EM/Mains

Temperature

T-Case Maximum (Nom)	75 °C

Controls and Dimming

Dimmable	No

Mechanical and Housing

Bulb Finish	Frosted
Bulb Material	Plastic
Product Length	115 mm
Bulb Shape	PL-C
Net Weight (Piece)	0.061 kg

Approval and Application

Energy Efficiency Class	D
Energy Saving Product	Yes
Approval Marks	RoHS compliance
Energy Consumption kWh/1000 h	6 kWh
EPREL Registration Number	2154071
CE mark	Yes
EU RoHS compliant	Yes
Flickering value (PstLM) - Flickering value as per EN 61000-3-3	1
Stroboscopic effect visibility measure (SVM)	0.4
Ambient temperature range	-20 to +35 °C


Application Conditions

can it be used in closed luminaires	Yes
Wireless Technology	Not applicable

Product Data

Order product name	CorePro LED PLC 360D 5.9W 3CCT 2P G24d
Full product name	CorePro LED PLC 360D 5.9W 3CCT 2P G24d
Full product code	872110303501100
Order code	929004252802
Material Nr. (12NC)	929004252802
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8721103035011
Numerator - Packs per outer box	10
EAN/UPC - Case	8721103035028


Dimensional drawing




D	D1	A1	A2	A3
35mm	35mm	65mm	115mm	137mm

Product	D1	D	A1	A2	A3
CorePro LED PLC 360D 5.9W 3CCT 2P G24d	35 mm	35 mm	65 mm	115 mm	137 mm


Photometric data



Spectral Power Distribution Colour - CorePro LED PLC 360D 5.9W 3CCT 2P G24d




General uniform lighting - CorePro LED PLC 360D 5.9W 3CCT 2P G24d




Light Distribution Diagram - CorePro LED PLC 360D 5.9W 3CCT 2P G24d


Lifetime




Life Expectancy Diagram




FailureRate



Lumen Maintenance Diagram - CorePro LED PLC 360D 5.9W 3CCT 2P G24d



LifetimeVsTc



Lumen Maintenance Diagram - CorePro LED PLC 360D 5.9W 3CCT 2P G24d

Related Documents

Documents and certificates	Document Name	Download
Installation Instructions	P0047389-reference-control-INI.pdf	Download
Environmental Product Declaration	Philips-CorePro-LED-PLC-360D-3CCT-2P-COMF-7904616-Ref-929004253002-EPD.pdf	Download
Installation Instructions	online-QIG-for-324166242332-Installation-guide-INI.pdf	Download

Photometry and lighting design	Document Name	Download
IES File	CorePro-LED-PLC-360D-5-9W-3CCT-2P-G24d-9290042528-IES.IES	Download

© 2026 Signify Holding. All rights reserved. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.