Supplied c/w Remote Driver



















	Code	Lamp	Description
	AERMLED2/120/CW	LED	58W - Cool White
	AERMLED2/120/WW	LED	58W - Warm White
	AERMLED2/120/DL	LED	58W - Daylight
Emergency	AIRMLED/POD/3NM/ST	LED	5W - Panel Pod Self-Test Emergency
Sensor	AIRMLED/POD/MWS		1W - Microwave Sensor
Option	/DD	Digital Dimming (DD1/DD2/DD3)	
Accessory	AERMLED/120/SMF	1200x600 Surface Mounting Frame	

- High performance maintenance free LED panel
- TPa as standard
- 60W panel outperforms 3x28W T5
- Cool white, warm white and daylight options
- White anodised aluminium frame for visual compatibility with ceiling grid
- Low glare and even light distribution for multiple applications
- Panel Pod Self-Test emergency option
- Panel Pod sensor option
- Powered by Philips
- LED lifespan L90 52,000 hours

AERMLED/120 Dimensions (mm) L1195 x W595 x H10

See p430 for more information on Panel Pod Emergency and Panel Pod Sensor

LED Information

Total (Watts)	58W			
Lumens Delivered				
Cool White	5780lm			
Warm White	5363lm			
Daylight	5646lm			
Lm/W Cool White	100lm			
Lm/W Warm White	93lm			
Lm/W Daylight	97lm			
CRI	Ra 80			
CCT Cool White	4000K			
CCT Warm White	3000K			
CCT Daylight	6500K			
Input	230V			
Hertz	50/60Hz			
Operating Temp	-20°C to 40°C			







^{*} Subject to ceiling/installation types

^{*} Not applicable to surface/suspended applications