

Ceiling mounted occupancy detectors - Slave devices

PD9-SDB

Product Information

- Slave device sensor especially for moisture-proof applications, suitable to miniature occupancy detector PD9-M-1C-SDB-IP65-FC
- For extending the detection area of a Master device

Technical Data

Dimensions:	Ø 36 x 28 mm
Detection area:	horizontal 360° (Ceiling mounting)
Range:	max. Ø 10 m across max. Ø 6 m towards max. Ø 4 m seated
Monitored area (tangential movement):	78 m ² / 2.5 m mounting height
Mounting height min./max./recommended:	2 m / 5 m / 2.5 m
Degree / class of protection:	IP65 / Class III
Cable length:	350 cm

Description

Description	Colour	Part number	EAN number
PD9-S-SDB-FC	white, similar to RAL9010	92915	4007529929153

Accessory

Description	Colour	Part number	EAN number
Cover IP65	transparent	92958	4007529929580
Cover ring PD9 Ø 36 mm	anthracite glossy	92235	4007529922352
Cover ring PD9 Ø 36 mm	white glossy	92238	4007529922383

Description	Colour	Part number	EAN number
Cover ring PD9 Ø 36 mm	silver glossy	92237	4007529922376
Cover ring PD9 Ø 45 mm	white mat	92327	4007529923274
Cover ring PD9 Ø 45 mm	silver mat	92346	4007529923465
Square design frame PD9-FC	pure white mat, similar to RAL9010	92993	4007529929931

© 2022 B.E.G. Brück Electronic GmbH