



MASTER PL-C 4 Pin



MASTER PL-C 18W/840/4P 1CT/5X10BOX

Energy-saving compact fluorescent lampsCompact long-arc low-pressure mercury discharge lampEnvelope consists of 4 parallel narrow fluorescent tubes

Warnings and Safety

- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position as well as applied HF control gear
- · Shorter lamp life when often switching and not well pre-heated electrodes
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information			
Cap base	G24Q-2 [G24q-2]		
Life to 50% failures preheat (nom.)	13000 h		
LSF preheat 2,000 hours rated	99 %		
LSF preheat 4,000 hours rated	98 %		
LSF preheat 6,000 hours rated	97 %		
LSF preheat 8,000 hours rated	90 %		
	Sphere		
Light Technical			
Colour Code	840 [CCT of 4,000 K]		
Luminous flux (nom.)	1200 lm		
Luminous flux (rated) (nom.)	1200 lm		
Colour designation	Cool White (CW)		
Chromaticity coordinate X (nom.)	0.38		
Chromaticity coordinate Y (nom.)	0.38		
Correlated Colour Temperature (Nom)	4000 K		

67 lm/W
80
92 %
87 %
83 %
81 %
18.4 W
0.230 A
28 °C
Yes

MASTER PL-C 4 Pin


Mechanical and Housing	
Cap-base information	4P
Approval and Application	
Energy Efficiency Class	G
Mercury (Hg) content (max.)	1.4 mg
Mercury (Hg) content (nom.)	1.4 mg
Energy consumption kWh/1,000 hours	19 kWh
	423303
Product Data	

871150062334870

Order product name	MASTER PL-C 18W/840/4P 1CT/5X10BOX	
EAN/UPC – product	8711500623348	
Order code	62334870	
Local order code	18PLC8404PIN	
SAP numerator - quantity per pack	1	
Numerator – packs per outer box	50	
SAP material	927907284040	
SAP net weight (piece)	55.300 g	
ILCOS code	FSQ-18/40/1B-E-G24q=2	

Dimensional drawing

Full product code




 Product
 D (max)
 D (max)
 A (max)
 B (max)
 C (max)

 MASTER PL-C 18W/840/P
 27.1 m
 27.1 m
 10.5 m
 12.0 m
 12.9 m


 1C/5X108DX
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2
 2

PL-C 18W/840/4P

Photometric data




Lightcolour /840





MASTER PL-C 4 Pin

Lifetime





☐ 100 IN			
% 100			
	1		

LDLE_PLC4P_0002-Life expectancy diagram

LDLM_PLC4P_0001-Lumen maintenance diagram



© 2021 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2021, September 2 - data subject to change