



MASTER PL-C 2 Pin



MASTER PL-C 18W/840/2P 1CT/5X10BOX

Energy-saving compact fluorescent lampsCompact long-arc low-pressure mercury discharge lampEnvelope consists of 4 parallel narrow fluorescent tubes

Warnings and Safety

- \cdot Use only with electromagnetic control gear
- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position
- · Dimming is not possible
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information	
Cap base	G24D-2 [G24d-2]
Life to 10% failures (nom.)	6500 h
Life to 50% failures (nom.)	10000 h
LSF 2000 h Rated	99 %
LSF 4000 h Rated	98 %
LSF 6000 h Rated	92 %
LSF 8000 h Rated	78 %
	Sphere
Light Technical	
Colour Code	840 [CCT of 4,000 K]
Luminous flux (nom.)	1200 lm
Luminous flux (rated) (nom.)	1200 lm
Colour designation	Cool White (CW)
Chromaticity coordinate X (nom.)	0.38

Chromaticity coordinate Y (nom.)	0.38
Correlated Colour Temperature (Nom)	4000 K
Luminous efficacy (rated) (nom.)	67 lm/W
Colour rendering index (nom.)	80
LLMF 2000 h Rated	92 %
LLMF 4000 h Rated	87 %
LLMF 6000 h Rated	83 %
LLMF 8000 h Rated	81 %
Operating and Electrical	
Power (Rated) (Nom)	18.3 W
Lamp current (nom.)	0.230 A
Temperature	
Design temperature (nom.)	28 ℃


Datasheet, 2021, September 2 data subject to change

MASTER PL-C 2 Pin

Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Cap-base information	2P
Approval and Application	
Energy Efficiency Class	G
Mercury (Hg) content (max.)	1.4 mg
Mercury (Hg) content (nom.)	1.4 mg
Energy consumption kWh/1,000 hours	19 kWh
	423284

Product Data	
Full product code	871150062093470
Order product name	MASTER PL-C 18W/840/2P 1CT/5X10BOX
EAN/UPC – product	8711500620934
Order code	62093470
Local order code	18PLC8402PIN
SAP numerator – quantity per pack	1
Numerator – packs per outer box	50
SAP material	927905784040
SAP net weight (piece)	57.800 g
ILCOS code	FSQ-18/40/1B-I-G24d=2


Dimensional drawing




PL-C 18W/840/2P



Photometric data




Lightcolour /840



Lightcolour /840


MASTER PL-C 2 Pin


Lifetime





LDLE_PLC2P_0001-Life expectancy diagram





LDLM_PLC2P_0001-Lumen maintenance diagram



© 2021 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.