



# **MASTER PL-C 2 Pin**



## **MASTER PL-C 10W/827/2P 1CT/5X10BOX**

Energy-saving compact fluorescent lampsCompact long-arc low-pressure mercury discharge lampEnvelope consists of 4 parallel narrow fluorescent tubes

#### **Warnings and Safety**

- $\boldsymbol{\cdot}$  Use only with electromagnetic control gear
- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position
- · Dimming is not possible
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

#### **Product data**

General Information					
Cap base	G24D-1 [ G24d-1]				
Life to 10% failures (nom.)	6500 h				
Life to 50% failures (nom.)	10000 h				
LSF 2000 h Rated	99 %				
LSF 4000 h Rated	98 %				
LSF 6000 h Rated	92 %				
LSF 8000 h Rated	78 %				
	Sphere				
Light Technical					
Colour Code	827 [ CCT of 2,700 K]				
Luminous flux (nom.)	600 lm				
Luminous flux (rated) (nom.)	600 lm				
Colour designation	Incandescent White				
Chromaticity coordinate X (nom.)	0.463				

Chromaticity coordinate Y (nom.)	0.42
Correlated Colour Temperature (Nom)	2700 K
Luminous efficacy (rated) (nom.)	60 lm/W
Colour rendering index (nom.)	82
LLMF 2000 h Rated	92 %
LLMF 4000 h Rated	87 %
LLMF 6000 h Rated	83 %
LLMF 8000 h Rated	81 %
Operating and Electrical	
Power (Rated) (Nom)	10.4 W
Lamp current (nom.)	0.190 A
Temperature	
Design temperature (nom.)	28 °C


Datasheet, 2021, September 2 data subject to change

## **MASTER PL-C 2 Pin**

Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Cap-base information	2P
Approval and Application	
Energy Efficiency Class	G
Mercury (Hg) content (max.)	1.4 mg
Mercury (Hg) content (nom.)	1.4 mg
Energy consumption kWh/1,000 hours	11 kWh
	423273

Product Data				
Full product code	871150070681270			
Order product name	MASTER PL-C 10W/827/2P 1CT/5X10BOX			
EAN/UPC – product	8711500706812			
Order code	70681270			
Local order code	10PLC8272PIN			
SAP numerator – quantity per pack	1			
Numerator – packs per outer box	50			
SAP material	927903882740			
SAP net weight (piece)	45.000 g			
ILCOS code	FSQ-10/27/1B-I-G24d=1			


## Dimensional drawing




MASTER PL-C 10W/827/2P	27.1 mm	27.1 mm	75.5 mm	95.0 mm	117.4 mm
1CT/5X10BOX					

D (max) D1 (max) A (max) B (max) C (max)

## Photometric data






Lightcolour /827

Lightcolour /827

Product


## **MASTER PL-C 2 Pin**


#### Lifetime





#### LDLE\_PLC2P\_0001-Life expectancy diagram





LDLM\_PLC2P\_0001-Lumen maintenance diagram



© 2021 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.