



MASTER PL-L 4 Pin



MASTER PL-L 18W/840/4P 1CT/25

Energy-saving compact fluorescent lamps Compact long-arc low-pressure mercury discharge lamp Envelope consists of 2 parallel fluorescent tubes

Warnings and Safety

- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position as well as applied control gear
- Shorter lamp life when often switching and not well pre-heated electrodes
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data


General Information		Sphere	
Cap base	2G11 [2G11]	Light Technical	
Life to 10% failures (nom.)	10000 h	Colour Code	840 [CCT of 4,000 K]
Life to 50% failures (nom.)	15000 h	Luminous flux (nom.)	1200 lm
Life to 50% failures preheat (nom.)	20000 h	Luminous flux (rated) (nom.)	1200 lm
System description	na [-]	Colour designation	Cool White (CW)
LSF 2000 h Rated	99 %	Chromaticity coordinate X (nom.)	0.38
LSF 4000 h Rated	98 %	Chromaticity coordinate Y (nom.)	0.38
LSF 6000 h Rated	96 %	Correlated Colour Temperature (Nom)	4000 K
LSF 8000 h Rated	94 %	Luminous efficacy (rated) (nom.)	67 lm/W
LSF 12000 h Rated	80 %	Colour rendering index (nom.)	80
LSF preheat 2,000 hours rated	99 %	LLMF 2000 h Rated	94 %
LSF preheat 4,000 hours rated	99 %	LLMF 4000 h Rated	93 %
LSF preheat 6,000 hours rated	98 %	LLMF 6000 h Rated	92 %
LSF preheat 8,000 hours rated	97 %	LLMF 8000 h Rated	91 %
LSF preheat 16,000 hours rated	82 %	LLMF 12000 h Rated	90 %
LSF preheat 20,000 hours rated	50 %		

MASTER PL-L 4 Pin

LLMF 16000 h Rated	90 %
LLMF 20000 h Rated	90 %
Operating and Electrical	
Power (Rated) (Nom)	18.0 W
Lamp current (nom.)	0.375 A
Temperature	
Design temperature (nom.)	30 °C
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Cap-base information	4P
Approval and Application	
Energy Efficiency Class	G

Mercury (Hg) content (max.)	2 mg
Mercury (Hg) content (nom.)	2.0 mg
Energy consumption kWh/1,000 hours	18 kWh
	423263
Product Data	
Full product code	871150070669040
Order product name	MASTER PL-L 18W/840/4P 1CT/25
EAN/UPC – product	8711500706690
Order code	70669040
Local order code	18PLL840
SAP numerator – quantity per pack	1
Numerator – packs per outer box	25
SAP material	927903008470
SAP net weight (piece)	60.900 g
ILCOS code	FSD-18/40/1B-E-2G11


Dimensional drawing



PL-L 18W/840/4P

Product	D (max)	D1 (max)	A (max)	B (max)	C (max)
MASTER PL-L 18W/840/4P 1CT/25	39.0 mm	18.0 mm	194.2 mm	220 mm	226.6 mm

Photometric data



Lightcolour /840

Lightcolour /840

MASTER PL-L 4 Pin

