

These instructions should be read carefully and retained after installation for further reference and maintenance

Safety Instructions

- Before installation or maintenance ensure that the mains supply to the luminaire is switched off and the circuit supply fuses are removed or circuit breaker turned off.
- It is recommended that a qualified electrician is consulted or used for the installation of this luminaire and installed to the current edition of the IEE wiring regulations.
- This luminaire is only suitable to be installed outside of Zone 2 in a bathroom.
- Check that the total load on the circuit, including this luminaire, does not exceed the rating of the circuit cable, fuse or circuit breaker.
- This light fitting must be installed in accordance with the current edition of the IEE Wiring Regulations BS7671.

If in doubt, contact a qualified electrician.

Installation

- Remove the two screws from the rear of the luminaire and remove the base.
- Remove the diffuser by squeezing in on it in line with the retaining clips and pulling the diffuser away from the body.
- Offer the luminaire to the mounting surface and mark out the fixing points.
- Feed the supply cable through the base and terminate the cables into the terminal block, ensuring the correct polarity is observed.
- Return the base to the luminaire and replace the 2 screws removed earlier.
- Offer the luminaire to the mounting surface and fit securely.
- Replace the diffuser, ensuring the retaining clips are properly positioned.

Operating Instructions

- When using the shaver socket, ensure that the shaver plug is fully inserted into the socket and that the Voltage Selection Switch is in the appropriate position.
- The shaver socket is not intended for continuous use or loads exceeding 20VA.
- Turn the light on/off by using the pull cord. This will not affect the operation of the shaver socket.

Specification

Power Supply	240V 50Hz	IP Rating	IP20
Shaver Socket Output	Dual Voltage (230V / 115V)	Construction	Class I
Lamp Type	LED	Lamp Wattage	8W Max.