



Wire Rocker Plate Switches

Description

This uniquely shaped range is easy to install, has clear white terminal markings, wide rockers and is supplied in individual protective bags.

This range of plateswitches do not have to be de-rated for fluorescent loads.

Features

- Unique slim profile with curved top and bottom edges
- Wide, concave rockers
- Hidden fixing screws
- Only one size 4mm screwdriver needed
- Clear white markings
- Terminals have large lead-ins
- Removable rocker
- 25-year guarantee

Range

| 1g 2w | S1345 |
|--------------|-------|
| 2g 2w | S1346 |
| 3g 2w | S1347 |
| Intermediate | S1348 |

Technical Specification

Voltage rating 250Vac Current Rating 10A X Rated

Contact gap 3mm

Frontplate material Urea formaldehyde

Urea flammability classification UL94 grade V-0

No user serviceable parts

Back Boxes

Minimum recommended depth

| | Flush | Dry lining | Surface |
|------|-------|------------|---------|
| | 25mm | 35mm | 25mm |
| 1-3g | DB152 | DB2540 | V1220/E |

Standards

BS 60669-1:2000

Terminal Capacity

| | 2.5mm² | 4mm² | 6mm² | 10mm² |
|---|--------|------|------|-------|
| L | 5 | 4 | 2 | 1 |