


Cooker Control Units



Description

This uniquely shaped range, in the Deta Slimline style, is easy to install with coloured terminals, clear white terminal markings and is supplied in individual protective bags.

This wide range includes neon versions, and an option of red or white switches.

Features

- Unique slim profile with curved top and bottom edges
- Concave rockers
- Switches rated at 45A
- Only one size 4mm screwdriver needed
- Terminals have clearly embossed and white printed markings
- Colour coded terminals
- Neon versions available
- 2 earth terminals
- Terminals have large lead-ins
- 25-year guarantee

Technical Specification

Voltage rating	250Vac
Current Rating	45A
Contact gap	3mm
Frontplate material	Urea formaldehyde

Urea flammability classification UL94 grade V-0

No user serviceable parts

Standards

- BS 4177: Part 4

Range

45AMP

Cooker control unit – Red Rocker	S1302
Cooker control unit, neon – Red Rocker	S1302P
Cooker control unit – White Rocker	S1312
Cooker control unit, neon – White Rocker	S1312P
Cooker cable outlet	S1217

Back Boxes

Minimum recommended depth

	Flush 47mm	Dry lining 46mm	Surface 46mm
1g	DB167	DB2542	V1228
2g	DB168	DB2543	V1229

Terminal Capacity

	6mm ²	10mm ²
L & N	2	1