


Blank and Connection Plates



Description

This uniquely shaped, easy to install, range is designed to match the Deta Slimline range of accessories.

Connection plates with coloured terminals; each product is supplied in individual protective bags.

Features

- Unique slim profile with curved top and bottom edges
- Only one size 4mm screwdriver needed
- Colour coded terminals
- Dual terminals of live, neutral and earth
- Large terminal capacity
- 25-year guarantee

Technical Specification

Voltage rating	250Vac
Current Rating	25A
Frontplate material	Urea formaldehyde

Urea flammability classification UL94 grade V-0

No user serviceable parts

Range

1g blank plate - White	S1200
2g blank plate - White	S1201
25A connection plate with flex outlet	S1215
25A connection plate, no flex outlet	S1216
45A cooker cable outlet	S1217

Back Boxes

Minimum recommended depth

	Flush 25mm	Dry Lining 35mm	Surface 25mm
1g	DB162	DB254	V1221
2g	DB163	DB2541	V1223
	Flush 47mm	Dry Lining 46mm	Surface 45mm
S1217	DB167	DB2542	V1228

Standards

- BS 5733 : 2010+A1:2014

Terminal Capacity

	2.5mm ²	4mm ²	6mm ²	10mm ²
L & N	5	3	2	1