


Plate Switches



Description

The elegantly styled Slimline Décor range is available in Chrome and Stainless Steel finishes, with either white or black insert colours.

Each product is supplied in its own polybag, protecting it up to the point of installation

Features

- Black or White inserts available
- Metal capped rockers
- Gasket pre-fitted to the accessory to prevent tarnishing
- Protective film on frontplate prevents damage during installation
- Captive and backed out terminals
- Terminals have clearly embossed and white printed markings
- Only one size 4mm screwdriver needed
- X-rated and can be used for switching inductive or fluorescent loads with de-rating
- Terminals have large lead-ins
- 25-year guarantee

Range

10A 1 gang 2-way	SD1203
10A 2 gang 2-way	SD1204
10A 3 gang 2-way	SD1205
10A 4 gang 2-way	SD1244
10A Intermediate	SD1246
10A 3 pole fan isolator	SD1247

Suffix finish with

Chrome	CH
Stainless Steel	SS
White or Black inserts	W or B

Technical Specification

Voltage rating	250Vac
Current Rating	10A
	X rated
Contact gap	3mm

No user serviceable parts

Back Boxes

Minimum recommended depth

	Flush 25mm	Dry lining 35mm
1-3g	DB162	DB2540
2g	DB163	DB2541

Standards

- BS EN 60669-1:2018

Terminal Capacity

	1mm ²	1.5mm ²	2.5mm ²	4mm ²
L	5	4	2	1