


Connection Units



Description

The elegantly styled Slimline Décor range is available in Chrome and Stainless Steel finishes, with either white or black insert colours.

Each product is supplied in its own polybag, protecting it up to the point of installation

Features

- Black or white inserts available
- Metal capped rockers
- Gasket pre-fitted to the accessory to prevent tarnishing
- Protective film on frontplate prevents damage during installation
- Lockable fuse carrier for safety isolation
- Captive fuse barrier
- Discreet neon versions
- Captive and backed out terminals
- Terminals have clearly embossed and white printed markings
- Clear white terminal markings
- Only one size 4mm screwdriver needed
- Most products have angled terminals to aid installation
- Terminals have large lead-ins
- 2 earth terminals
- 25-year guarantee

Technical Specification

Voltage rating	250Vac
Current Rating	13A
Contact gap	3mm

No user serviceable parts, except BS 1362 fuse links

Standards

- BS 1363 Part 4

Range

Unswitched spur	SD1360
Switched spur	SD1370
Switched spur with neon	SD1371
Switched spur with neon & flex outlet	SD1373

Suffix finish with

Chrome	CH
Stainless Steel	SS
White or Black inserts	W or B

Back Boxes

Minimum recommended depth

	Flush 35mm	Dry lining 35mm
1g	DB162	DB2540

Terminal Capacity

	2.5mm ²	4mm ²	6mm ²	10mm ²
L & N	4	3	2	1