


## Plateswitches



### Description

This uniquely styled range has concealed screws behind a smooth frontplate with an ultra slim profile.

### Features

- All plate switches are x-rated and can be used for switching inductive or fluorescent loads with de-rating
- Metal frontplates
- Concave rockers
- Only one size 4mm screwdriver needed
- Clear white markings
- Terminals have large lead-ins
- 25-year guarantee

### Range

10A 1 gang 2-way plate switch	8501
10A 2 gang 2-way plate switch	8502
10A 3 gang 3-way plate switch	8503
10A 4 gang 4-way plate switch	8504
10A intermediate plate switch	8506
10A 3 pole fan isolator switch	8507

### Suffix finish with

Chrome	CH
Stainless Steel	SS
White	WH
White or Black inserts	W or B

### Technical Specification

Voltage rating	250Vac
Current Rating	10A
	X Rated
Contact gap	3mm

No user serviceable parts

### Back Boxes

Minimum recommended depth

	Flush 25mm	Dry lining 35mm
1-3g	DB162	DB2547
4g	DB163	DB2548

### Standards

- BS 60669-1

### Terminal Capacity

	2.5mm <sup>2</sup>	4mm <sup>2</sup>	6mm <sup>2</sup>	10mm <sup>2</sup>
L	5	4	2	1