


Dimmer Switches



Features

- Colour matched knobs
- Protective film on front plate prevents damage during installation
- Colour matched knobs
- Protective film on front plate prevents damage during installation
- Spare dimmer knobs available
- Suitable for use with dimmable LED lamps, Halogen, and Incandescent Lamps
- Push on / push off control
- Suitable for Multiway dimming circuits when used with a push to make switch
- Dimmer automatically changes mode, to either Leading Edge (LE) or Trailing Edge (TE), to suit LED load
- Programmable to set desired brightness levels
- LED back light to indicate the dimming mode i.e. Leading or Trailing edge
- Ideal for controlling DETA range of Fire Rated Dimmable LED Downlights
- 2-year guarantee

Technical Specification

Voltage rating 250Vac
Frequency 50Hz

LED dimmers

- LED – 250W
- halogen – 350W
- Incandescent and ECO halogen – 350W

No user serviceable parts

Standards

- BS EN 60669-2-1

Description

This range of universal dimmers within the Deta Slimline Décor range can control mains voltage lamps.

Our LED versions are designed specifically with LED lighting in mind and are optimised to control our dimmable LED Fire Rated Downlights, as well as other leading brands of LED lamps, with minimal programming.

Range

LED Dimmer

1g 250W push on/off	SD1414
2g 250W push on/off	SD1415

Suffix finish with

Chrome	CH
Stainless Steel	SS

Back Boxes

Minimum recommended depth

	Flush 35mm	Dry Lining 35mm	Surface 33mm
SD1414	DB162	DB2540	V1221
SD1415	DB162	DB2540	V1221

Accessories

SP0004CH	Dimmer Knobs (Pack of 10)- chrome
SP0004SS	Dimmer Knobs (Pack of 10)- stainless steel
SP0002CH	50mm Length (Pack of 10) - chrome
SP0002SS	50mm Length (Pack of 10) - stainless steel
SP0003CH	75mm Length (Pack of 10) - chrome
SP0003	75mm Length (Pack of 10) - stainless steel

Terminal Capacity

	1mm ²	1.5mm ²
L	2	2