

FP100® BS 8592

Fire Resistant Single Core Cable. 450/750 V



Prysmian FP100® BS 8592 is the original fire resistant low voltage single core cable for use in steel conduits

KEY APPLICATIONS

FP100® BS 8592 is ideally suited to drawing into conduit installations that provide adequate mechanical protection and it forms the key part of a wiring system for evacuation and fire fighting applications.

Green/Yellow is also suitable as a separate earth.

FEATURES AND BENEFITS

- Ideal for rewiring existing steel conduit and upgrade to a fire resistant system or where the added mechanical protection or utilisation of a steel conduit is required
- Tough robust insulation prevents damage during installation
- Low smoke and corrosive gas emissions Low Smoke, Zero Halogen (LSOH®)
- Manufactured under ISO 9001 Quality management systems
- 1.5 - 6mm² fire tested to BS 8519:2020 Annex D (Manufacturer's test reports available upon request)

ADDITIONAL TECHNICAL SUPPORT

- [FAQ's](https://uk.prysmiangroup.com/technical-area/faqs) - uk.prysmiangroup.com/technical-area/faqs
- [Technical email](mailto:tech.info@prysmiangroup.com) - tech.info@prysmiangroup.com
- [Live Chat](https://uk.prysmiangroup.com/technical-area) - uk.prysmiangroup.com/technical-area
- Technical hotline: 02380 295222

STANDARDS



BS 8592

IEC 60331-3

BS EN 50200 - PH120

BS 8434-2

BS EN 60332-1-2

BS EN 61034-2

BS EN 60754-1

BS EN 60228

Construction Standard

Fire Resistant Test

Fire Resistant Test - Flame & Shock - 120 Minutes

Fire Resistant Test - Flame, Shock & Water - 120 Minutes

Flame Propagation - Single Cable

Smoke emission

Corrosive and acid gas

Conductors

CONSTRUCTION

Conductor material

Copper

Conductor surface

Bare

Core insulation material

Mica + polymer

APPLICATIONS PROPERTIES

Nominal voltage U0 [V]	450
Nominal voltage U [V]	750
Flame retardant	In accordance with BS EN 60332-1-2
Halogen free	Yes
Low smoke	Yes
Max. conductor temperature [°C]	90
Min. Operation temperature [°C]	-25
Min. Installation temperature [°C]	0
Max. Installation temperature [°C]	80
Bending radius (rule)	6D

COLOURS

A range of insulation colours are available, including green/yellow

CURRENT RATINGS

Refer to table 4E1 of BS 7671 Requirements for Electrical Installations. IET Wiring Regulations

Note: Where a conductor operates at a temperature exceeding 70°C it shall be ascertained that the equipment connected to the conductor is suitable for the conductor operating temperature

TECHNICAL DATA

Nominal cross section conductor [mm ²]	Conductor category	Nominal thickness insulation [mm]	Nominal outer diameter [mm]	Cable weight [kg/km]	Conductor resistance at 20° C [Ohm/km]	Embodied Carbon [CO ₂ e kg/km]
1.5	Class 2 = stranded	0.7	3.6	26	12.1	36
2.5	Class 2 = stranded	0.8	4.2	39	7.41	46
4	Class 2 = stranded	0.8	4.7	53	4.61	54
10	Class 2 = stranded	1	6.6	125	1.83	118
16	Class 2 = stranded	1	7.2	180	1.15	102
25	Class 2 = stranded	1.2	9	280	0.727	155
35	Class 2 = stranded	1.2	10.5	380	0.524	178
50	Class 2 = stranded	1.4	12.2	520	0.387	209
70	Class 2 = stranded	1.4	13.4	710	0.268	310

*The embodied carbon figure is taken from a single product in the range, for more information on how we calculate our embodied carbon figure visit here: <https://uk.prysmiangroup.com/embodied-carbon>