

Calinor LED Polycarbonate Floodlight

Supplied c/w Integral Driver

- Compact and economic polycarbonate LED floodlight
- Warm and Cool white options
- 30W LED comparable light output of 35W HQI
50W LED exceeds performance of 70W HQI
- Polished faceted reflector and textured glass for optimum performance
- Pre-wired with 1 metre of rubber insulated cable for ease of installation
- PIR versions complete with manual override facility
- LED lifespan L70 20,000 hours
- Non-dimmable



423



5 - 12 Metres
10 Seconds - 8 Minutes
3 Lux - PC Off
Detection Angle - 120°



ACALED30




ACALED30/PIR




ACALED50




ACALED50/PIR




ACALED30



ACALED30/PIR



ACALED50



ACALED50/PIR

LED Information

Cool White Warm White

Total (Watts)	30W	50W
Lumens Delivered		
30W	2708lm	2701lm
50W	4770lm	4511lm
Lm/W 30W	97lm	97lm
Lm/W 50W	99lm	94lm
CRI	Ra 80	
CCT	4000K	
	3000K	
Input	230V	
Hertz	50Hz	
Operating Temp	-15°C to 40°C	

	Code	Lamp	Description	Windage
Standard	ACALED30	LED	30W - Cool White	0.03
PIR	ACALED30/PIR	LED	30W c/w PIR - Cool White	0.05
Standard	ACALED50	LED	50W - Cool White	0.05
PIR	ACALED50/PIR	LED	50W c/w PIR - Cool White	0.07
Standard	ACALED30/WW	LED	30W - Warm White	0.03
PIR	ACALED30/WW/PIR	LED	30W c/w PIR - Warm White	0.05
Standard	ACALED50/WW	LED	50W - Warm White	0.05
PIR	ACALED50/WW/PIR	LED	50W c/w PIR - Warm White	0.07



Warrington: +44 (0) 1942 433333
Belfast: +44 (0) 2890 773750

