

Eden LED Floodlight

Supplied c/w Integral Driver



AEDELED10/CW



AEDELED10/WW/PIR



AEDELED20/WW




AEDELED20/WW/PIR




10 Metres
10 Seconds - 7 Minutes
3 - 2000 LUX
Detection Angle - 120°


- Compact and economic aluminium LED floodlight
- 10W ideal for halogen replacement
- 20W exceeds performance of 20W HQI
- Bracket design allows installation without removing mounting bracket
- PIR versions complete with manual override facility
- Pre-wired with 1 metre of rubber insulated cable for ease of installation
- Cool white and warm white options available
- LED lifespan L90 36,000 hours
- Non-dimmable




AEDELED10/WW



AEDELED10/WW/PIR



AEDELED20/WW



AEDELED20/WW/PIR

LED Information

	Cool White	Warm White
Total (Watts)		10W
		20W
Lumens Delivered		
10W	953lm	894lm
20W	1834lm	1720lm
Lm/W 10W	95lm	89lm
Lm/W 20W	92lm	86lm
CRI	Ra 80	
CCT	4000K	
	3000K	
Input	220-240V	
Hertz	50/60Hz	
Operating Temp	-20°C to 40°C	

	Code	Lamp	Description	Windage
Standard	AEDELED10/CW	LED	10W - Cool White	0.02
PIR	AEDELED10/CW/PIR	LED	10W c/w PIR - Cool White	0.02
Standard	AEDELED20/CW	LED	20W - Cool White	0.02
PIR	AEDELED20/CW/PIR	LED	20W c/w PIR - Cool White	0.03
Standard	AEDELED10/WW	LED	10W - Warm White	0.02
PIR	AEDELED10/WW/PIR	LED	10W c/w PIR - Warm White	0.02
Standard	AEDELED20/WW	LED	20W - Warm White	0.02
PIR	AEDELED20/WW/PIR	LED	20W c/w PIR - Warm White	0.03