

Matrix LED CCT Linklight

Supplied c/w Integral Driver



- CCT Selectable LED linklight with integral driver
- Side mounted switch allows installer the choice of 3000K or 4000K colour temperature options
- Moulded spine fitted with integral switch and fixed diffuser
- c/w angled and straight fixing clips
- Supplied c/w 1.5m mains power lead
- Linkable up to a maximum of twelve fittings
- LED lifespan L70 25,000 hours
- Non-dimmable

LED Information

	Cool White	Warm White
Total (Watts)	3W	
	7W	
	13W	
	18W	
Lumens Delivered	290lm	272lm
	712lm	696lm
	1320lm	1268lm
	1844lm	1724lm
Lm/W	97lm	91lm
	102lm	99lm
	102lm	98lm
	102lm	96lm
CRI	Ra 80	
CCT	4000K	
	3000K	
Input	230V	
Hertz	50/60Hz	
Operating Temp	-10°C to 40°C	

Code	Lamp	Description	Length	Width	Depth
AMALED20/CCT	LED	3W - 4000K/3000K	220	22.8	38.4
AMALED50/CCT	LED	7W - 4000K/3000K	525	22.8	38.4
AMALED80/CCT	LED	13W - 4000K/3000K	858	22.8	38.4
AMALED120/CCT	LED	18W - 4000K/3000K	1158	22.8	38.4

Accessories	A250TLL/T5	250mm Link Lead
	A500TLL/T5	500mm Link Lead
	A1000TLL/T5	1000mm Link Lead

