



# Beacon LED Fixed Emergency Downlight

Supplied c/w Remote Driver and Battery Pack



- LED Non-Maintained fixed polycarbonate downlight
- 3 hour emergency output
- Power and green charge LED are discreetly incorporated within the head
- 123° beam angle



\* 1 lux minimum must be used for all marked emergency escape routes, to be measured down the centre line of the escape route itself

\*\* 0.5 lux minimum must be used for areas larger than 60m<sup>2</sup>, the maximum value is to be measured across the area excluding 0.5 metre border around the edge of the room

\*\*\* Explanation of the symbols:-

**Transverse - Wall**

Distance to wall from side of fitting

**Transverse - Transverse**

Side to side spacing

**Axial - Wall**

Distance to wall from end of fitting

**Axial - Axial**

End to end spacing

**LED Information**

Total (Watts)	5W
Lumens Delivered	
Emergency Mode	316lm
Beam Angle	123°
CCT	6500K
Input	230V
Hertz	50Hz
Operating Temp	0°C to 40°C

***	Escape route 2 metres wide (1 Lux minimum) *			
	***	***	***	***
Mounting Height (M)	Transverse to Wall	Transverse to Transverse	Axial to Wall	Axial to Axial
2.5	-	-	3	9.5
4	-	-	3.3	11.5
6	-	-	-	-

***	Open (Anti-Panic) area (0.5 Lux Minimum) **			
	***	***	***	***
Mounting Height (M)	Transverse to Wall	Transverse to Transverse	Axial to Wall	Axial to Axial
2.5	3.5	8.9	3.5	8.9
4	4	11.4	4	11.4
6	4.5	12.9	4.5	12.9

Code	Lamp	Description
ABFLED/3NM	LED	5W Non-Maintained

<b>Accessory</b>	ASBP/9	3.6V 4.5Ah Ni-Cd Replacement Battery
------------------	--------	--------------------------------------

