

Helder LED Circular Bulkhead

Supplied c/w Integral Driver



AHELED/CB



AHELED/CW/PIR



AHELED/EB



Adjustable PIR allows control over the time delay and LUX setting.




Adjustable time
between 10 seconds
to 5 minute



Adjustable LUX
between
10 - 2000 LUX



Max 10 metres
10 seconds to 5 minutes
10 - 2000 LUX



	Code	Lamp	Description
Standard	AHELED/CB	LED	14W - Black - Cool White
	AHELED/CW	LED	14W - White - Cool White
PIR	AHELED/CB/PIR	LED	14W - Black - Cool White - PIR
	AHELED/CW/PIR	LED	14W - White - Cool White - PIR
Standard Eyelid	AHELED/EB	LED	14W - Black - Cool White
	AHELED/EW	LED	14W - White - Cool White
PIR Eyelid	AHELED/EB/PIR	LED	14W - Black - Cool White - PIR
	AHELED/EW/PIR	LED	14W - White - Cool White - PIR

LED Information

Total (Watts)	14W
Lumens Delivered	
Standard	972lm
Eyelid	529lm
PIR	1011lm
Lm/W	
Standard	70lm
Eyelid	38lm
PIR	72lm
CRI	Ra 80
CCT	4000K
Input	220-240V
Hertz	50/60Hz
Operating Temp	-20°C to 40°C