



Product Description: Borealis 40W Up/Down 400mm Halo Light

BOREALIS 40W 4000K-IRC80 4000lm DIAMETER 400mm - Circular luminaire, direct and indirect lighting, suspended or surface-mounted. Architectural lighting for installation in entrance halls, interior corridors, residential areas, etc.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour	SKU Type
300338	40	4000	4000	100	120	Black	Non Dimmable

Line Drawing

Polar Curve

Colour

Feature & Benefits

- Architectural luminaire for installation in entrance halls, interior corridors, commercial and residential areas
- Direct and indirect lighting providing a halo effect on the mounting surface
- Loop-in loop-out 3 pole connectors, Replaceable driver
- Can be surface, suspended or rod mounted
- L80B10 50,000hrs
- 5 Years Warranty
- 3 year onsite warranty (registration required) *Terms and conditions apply

Product Specs:

Input Voltage	220~240V AC
IP Rating	IP40
IK Rating	IK04
Overall Diameter (mm)	400
Projection (mm)	86
Product Type	Architectural Lighting
Operating Temp. (Max) °C	35°C

Input Frequency	50/60HZ
Lifetime L80 (Hours)	50000hrs
Width (mm)	400
Weight (Kg)	3.2
Height (mm)	86
Operating Temp. (Min) °C	-15°C

Compliance & Approvals:

Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.