




**Product Description:** Uni-Fit™ 10W Integrated IP44 Non-Dimmable Downlight


Performance and Value - that's what the Uni-Fit™ range of commercial downlights stands for. Featuring ThermoTec™ technology, integrated driver and high quality LED chips to deliver an outstanding lumen performance. The triac dimmable Uni-Fit™ range is the ideal cost effective solution for new or existing installations where traditional compact fluorescent downlights need upgrading to more efficient LED technology.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour	SKU Type
EN-DL10/30	10	3000	850	85	100	White	Non Dimmable
EN-DL10/40	10	4000	900	90	100	White	Non Dimmable


**Line Drawing**



**Polar Curve**



**Color**



White

## Product Features:

- Multiple sizes and wattages available to suit all new and retrofit installation lighting requirements
- ThermoTec™ technology utilises a combination of highly efficient LED light source, aluminium heat sinking and thermoplastic material for longer life and consistent performance
- Compact integrated driver for easy installation and shallow ceiling voids
- Life not affected by frequent switching e.g. when used with occupancy controls
- IP44 rated
- Pre-wired with 500mm 2 core cable
- 1.5kV surge protection
- 3 year warranty

## Product Specs:

Input Voltage	220~240V AC	Input Frequency	50/60HZ
Power Factor	0.5	IP Rating	IP44
Lifetime L70 (hrs)	25000	IK Rating	IK06
Lamp Base	None	Height (mm)	60
Overall Diameter (mm)	120	Weight (Kg)	0.161
Cutout Diameter (mm)	100	Product Type	Downlights
Operating Temp. (Min) °C	-20°C	Operating Temp. (Max) °C	40°C

## Compliance & Approvals:



## Warranty:

This product has a warranty period of 3 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.