


HORIZON LOUVRE

LED

CFL



-  White
HR_**W**
-  Titanium
HR_**X**
-  Satin Aluminium
HR_**F**



Size	HR2	HR3
A	283mm	353mm
B	113mm	122mm

LED / Lamp Types

- 28W & 38W 4-Pin, 3500K, GR10 Cap.
- B22 GLS (lamp not included, 100W max).
- 16W 2D 4-Pin, 3500K, GR8 Cap.
- 21W 2D 4-Pin, 3500K, GR10 Cap.
- 2 x 18W TC-D G24q-2 Cap.
- LED options.

Materials

- Body: 283mm/353mm vandal resistant polycarbonate with self-extinguishing fire properties.
- Diffuser/Fascia Ring: Vandal resistant polycarbonate in opal with self-extinguishing fire properties.
- Diffuser 2: (353mm circular) Vandal resistant polycarbonate clear fresnel lens with self extinguishing fire properties.
- Die cast aluminium option available (HR3 only).

Installation

- Wall or ceiling mount.
- BESA fixing and rear cable entry, 3 way mains terminal block, 4 way terminal block for emergency versions & photocell.
- Screw down lid.
- Photocell version - external use only.
- HI-LO PIR - 100% light output, dims to 10% during periods of inactivity.
- 2 x Conduit entry points (mini version only).

Standards

- IP65.
- IK10.
- 'F' Mark.
- CE.
- BS EN 60598.
- Class I.

Options

LED	Mini Horizon Louvre Code	Colour Finish	Diffuser	IP Rating	CRI	CCT	System Power	Delivered Lumens	Efficacy	Emergency	PIR	Photocell	HI-LO PIR	Dimmable
LED 600	HR2/BLL4LED600	Black	Premium Opal	IP65	80	4000K	7.4W	281.8lm	38lm/W		✓	✓	✓	
CFL	Mini Horizon Louvre Code	Colour Finish	Diffuser	IP Rating										
B22 GLS	HR2/BLL060	Black	Premium Opal	IP65										
16W HF	HR2/BLL516U6	Black	Premium Opal	IP65										
21W HF	HR2/BLL521U6	Black	Premium Opal	IP65										
LED	Horizon Louvre Code	Colour Finish	Diffuser	IP Rating	CRI	CCT	System Power	Delivered Lumens	Efficacy	Emergency	PIR	Photocell	HI-LO PIR	Dimmable
LED 1800	HR3/BLL4LED1800	Black	Premium Opal	IP65	80	4000K	17.8W	762lm	42.8lm/W	✓	✓	✓	✓	
CFL	Horizon Louvre Code	Colour Finish	Diffuser	IP Rating										
2 X 18W HF	HR3/BLL218U6	Black	Premium Opal	IP65										
28W HF	HR3/BLL528U6	Black	Premium Opal	IP65										
38W HF	HR3/BLL538U6	Black	Premium Opal	IP65										

Code Options (Add suffix to code)



3 Hour Maintained
Emergency
M



PIR
P



HI-LO PIR
HILO



Photocell
C



DALI / DSI Dim
-DDD



Anti Tamper Screws
T

Diffuser Option

Fresnel (Non LED only)

Change code

HR_**_K**

Body Option

Metal Base Option

Add to code

HR**3M/**