


A CURRENT	V VOLTAGE	Hz FREQUENCY	 6P+E	EARTH HL POS
--------------	--------------	-----------------	--	--------------------

# 7 Pole Plugs & Sockets

# CEE NORM

16	240	50 - 60	11634	9
32	240	50 - 60	11635	9
16	415	50 - 60	11542	6
32	415	50 - 60	11578	6



## Surface Mounting Socket Outlet

 Watertight

16	240	50 - 60	13330	9
32	240	50 - 60	13332	9
16	415	50 - 60	13331	6
32	415	50 - 60	13333	6



## Panel Mounting Socket Outlet

 Watertight

16	240	50 - 60	21711	9
32	240	50 - 60	21712	9
16	415	50 - 60	21667	6
32	415	50 - 60	21669	6



## Plug with Multi-Grip Cable Gland

- Multi-Grip cable gland system with moulded-in gasket

 Watertight

16	240	50 - 60	31512	9
32	240	50 - 60	31514	9
16	415	50 - 60	31513	6
32	415	50 - 60	31515	6



## Connector with Multi-Grip Cable Gland

- Multi-Grip cable gland system with moulded-in gasket

 Watertight

16	240	50 - 60		9
32	240	50 - 60		9
16	415	50 - 60	24309	6
32	415	50 - 60	24536	6



## Surface Mounting Appliance Inlet

 Watertight

16	240	50 - 60	16447	9
32	240	50 - 60	16448	9
16	415	50 - 60	16380	6
32	415	50 - 60	160087	6



## Surface Mounting Switched Interlocked Socket Outlet

 Watertight


16	240	50 - 60	21823	9
32	240	50 - 60	21811	9
16	415	50 - 60	21818	6
32	415	50 - 60	21600	6



## Special Plugs for Earth Monitoring 6 Pin (with 2 Shortened Pins) + E

 Watertight


# Dimensions



Amperes	<b>16</b>	<b>32</b>
Poles	7	7
a	90	118
b	170	225
c	77	101
d	137.5	1208
e	122	149
f	195	255
g	6.5	6.5
Ø h	5.5	8
i	M20	2x M25
k	M20 / 25	2x M25
Conductor mm <sup>2</sup> min	1.5	2.5
Conductor mm <sup>2</sup> max	4	10

## Surface Mounting Socket Outlet


 Watertight



Amperes	<b>16</b>	<b>32</b>
Poles	7	7
a	75	75
b	75	75
c	60	60
d	60	60
Ø e	5.5	5.5
f	7	8
h	35.5	50
i	57	65
k	93	106
Ø l	55	60
m	11.5	17
Conductor mm <sup>2</sup> min	1.5	2.5
Conductor mm <sup>2</sup> max	4	10

## Panel Mounting Socket Outlet


 Watertight




Amperes	<b>16</b>	<b>32</b>
Poles	7	7
Ø a	86	101
b	97	117
c	152	181
d	119	138.5
Ø e	21	27
Conductor mm <sup>2</sup> min	1	2.5
Conductor mm <sup>2</sup> max	2.5	6

## Plug with Multi-Grip Cable Gland

- Multi-Grip cable gland system with moulded-in gasket

 Watertight




Amperes	<b>16</b>	<b>32</b>
Poles	7	7
Ø a	86.5	101.5
b	168	200
c	93	107
Ø d	21	27
Conductor mm <sup>2</sup> min	1	2.5
Conductor mm <sup>2</sup> max	2.5	6

## Connector with Multi-Grip Cable Gland

- Multi-Grip cable gland system with moulded-in gasket


 Watertight



Amperes	<b>16</b>	<b>32</b>
Poles	7	7
a	84	90
b	84	75
c	136	139
d		123
ef		
Ø h		
i		
k		
l	111	
m	64	78
n	64	45
Ø o	5.5	5.5
p		
r		
Ø s	M20	M25
t	23	29

## Surface Mounting Appliance Inlet


 Watertight



Amperes	<b>16</b>	<b>32</b>
Poles	7	7
a	118	160
b	225	260
c	101	140
d	208	240
e	134	195
f	245	304
g	6.5	8.1
h	8	10
i	2x M25	1x M40
k	2x M25	1x M32/M40

## Surface Mounting Switched Interlocked Socket Outlet

 Watertight



Amperes	<b>16</b>	<b>32</b>
Poles	7	7
Ø a	86	101
b	97	117
c	152	181
d	119	138.5
Ø e	21	27
Conductor mm <sup>2</sup> min	1	2.5
Conductor mm <sup>2</sup> max	2.5	6

## Special Plugs for Earth Monitoring 6 Pin (with 2 Shortened Pins) + E

 Watertight