

DATASHEET

LEXINGTON SLIM PRO


Lexington Pro Slim LED Exit Box Maintained 3Hr

3 Hour Maintained / Non-Maintained Exit Box
 Supplied With Arrow Down Legend
 Slim Design



GENERAL INFORMATION	
Product Code	NLE/SLIM/M3
Product Range	Emergency
Product Category	Emergency
IP Rating	20
IK Rating	N/A
Warranty	5 Years Unlimited
DIMENSION/WEIGHT	
Dimensions Circular (DIA x H) (mm)	DIA=N/A, H=N/A
Dimensions Square/Rectangular (L x W x H) (mm)	L=320, W=28, H=185
Cut-out Size (mm)	N/A
Product Weight (Kg)	0.7
CONSTRUCTION	
Body Material	Polycarbonate
Body Colour	White
Optical Material	N/A
Optical Finish	N/A
Termination	4-Pole Terminal Block
Driver - Integral or Remote	Integral
PACKAGING	
Carton Dimensions (mm)	N/A
Quantity per Outer Carton	N/A
Total Weight incl. Carton (Kg)	N/A

LUMINAIRE PERFORMANCE	
Energy Rating	N/A
Luminaire Lumens (lm)	N/A
Power Consumption (W)	N/A
Efficacy	N/A
Operating Temp. (Min/Max)	0°C to - 25°C
LIGHT SOURCE	
Type	LED
Correlated Colour Temp.	N/A
Correlated Rendering Index (CRI)	N/A
Lumen Depreciation	L80 100000
SDCM	N/A
ELECTRICAL INPUT	
VOLTAGE (V)	220-240V AC
Operating Frequency	50
In Rush	N/A
Drivers per MCB*	N/A
Class	Class 1
Power Factor	N/A
Cable Entry	Back
ELECTRICAL OUTPUT	
Forward Current (mA)	N/A
Forward Voltage (Vf)	N/A
EMERGENCY DATA	
Mode of Operation	Maintained
Battery Duration	3 Hours
Battery Type	LiFePO4
Battery Specification	3.2V 1500mAh
Ballast Lumen Factor (BLF)	N/A
DIMMING	
DALI	N/A
OTHER	N/A
Switch Dim	N/A
Corridor Function	N/A
SENSORS	
Microwave	N/A
PIR	N/A
STANDARDS/APPROVALS	
CE Marked	Yes
Certificate of Conformity	Yes
Accreditations	N/A
BARCODE	
EAN NUMBER	5055943076532



* GUIDE ONLY

