

## Description

Starlet Recessed LED Round Panel Light c/w remote Plug & Play Driver



## General

Colour Options	White Bezel Only
Light Source	Non Replaceable LED Module
LED Expected Life	30,000 Hours Average Life
Product Warranty	3 Years from Date of Purchase
Mounting Method	Ceiling Recessed

## Electrical Parameters

Supply Voltage	220-240v AC
Frequency	50/60 Hz
Circuit Wattage	18W Including Driver
Circuit Current	0.1 Amps
Driver mA Rating	300mA
PFC	0.75
In Rush Current	0.15Amps Max Peak

## Classifications and Approvals

Earth Class	Class II, No Earth Required
IP Rating	IP20
Fire Rating (Part B)	No
Sound Insulating (Part E)	No
Air & Moisture Rated (Part C)	No
Efficiency Rated (Part L)	Yes Part L Compliant
Energy Rating	A+
CE Marked	Yes
Designed In Accordance to	BSEN60598, EN55015, EN61347

## Installation

Cut-out	210mm
Minimum Void	60mm
Insulation	Must Remain in Free Air Space
Working Ambient Temp.	-10°C to +30°C
Primary Connections	L & N Screw Down Terminals, Direct to Driver
Secondary Connections	Plug & Play Driver to Head Unit
Accessories	N/A

## Performance

Luminous Flux	1350 Lumens
Luminous Efficacy (Lm/W)	75 Lm/W
CCT	4000k
CRI (Ra)	Ra:80
Beam Angle	120°
Dimmable	No, Non Dimmable
Tilt/Rotate	No, Fixed Position Luminaire

## Construction

Main Chassis	Mild Steel
Trim/Bezel	Aluminium
Diffuser	Polystyrene
Lens	N/A
Heat Sink	Mild Steel
Finish Type	White Powder Coat Paint
Luminaire Weight	TBC

