

Eaton 222394

Catalog Number: 222394

Eaton Moeller® series PKZM4 Motor-protective circuit-breaker, Ir= 50 - 58 A, Screw terminals, Terminations: IP00 PKZM4-58

General specifications



Product Name

Eaton Moeller® series PKZM4 Motor-protective circuit-breaker

Catalog Number

222394

Model Code

PKZM4-58

EAN

4015082223946

Product Length/Depth

160 mm

Product Height

140 mm

Product Width

55 mm

Product Weight

1.136 kg

Certifications

CSA Class No.: 3211-05

IEC/EN 60947-4-1

CSA File No.: 165628

CSA-C22.2 No. 60947-4-1-14

UL Category Control No.: NLRV

VDE 0660

CE

CSA

IEC/EN 60947

UL File No.: E36332

UL

UL 60947-4-1

Product specifications

Features

Phase-failure sensitivity (according to IEC/EN 60947-4-1, VDE 0660 Part 102)

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be

Resources

Brochures

[eaton-motor-starters-system-xstart-brochure-br03407001en-en-us.pdf](#)

Catalogs

Product Range Catalog Switching and protecting motors

[eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf](#)

[Switching and protecting motors - catalog](#)

Characteristic curve

[eaton-manual-motor-starters-characteristic-pkzm4-characteristic-curve-002.eps](#)

[eaton-manual-motor-starters-pkzm4-characteristic-curve-002.eps](#)

[eaton-manual-motor-starters-tripping-characteristic-pkzm4-characteristic-curve-003.eps](#)

[eaton-manual-motor-starters-characteristic-pkzm4-characteristic-curve.eps](#)

Declarations of conformity

[DA-DC-00004953.pdf](#)

[DA-DC-00004960.pdf](#)

Drawings

[eaton-manual-motor-starters-circuit-breaker-pkzm4-dimensions.eps](#)

[eaton-manual-motor-starters-pkzm4-dimensions.eps](#)

[eaton-manual-motor-starters-pkzm4-3d-drawing.eps](#)

[eaton-manual-motor-starters-mounting-3d-drawing-002.eps](#)

[eaton-general-ie-ready-dilm-contactor-standards.eps](#)

[eaton-manual-motor-starters-circuit-breaker-pkzm4-3d-drawing.eps](#)

eCAD model

[ETN.222394.edz](#)

Installation instructions

[eaton-motors-starters-pkzm4-motor-protective-circuit-breaker-instruction-leaflet-il03407012z.pdf](#)

Installation videos

[WIN-WIN with push-in technology](#)

Manuals and user guides

[eaton-motor-protective-circuit-breaker-pkzm4-overload-monitoring-exe-manual-mn03402002z-de-de-en-us.pdf](#)

mCAD model

[DA-CD-pkzm4](#)

evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

Operating frequency

40 Operations/h

Pollution degree

3

Climatic proofing

Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78

Actuator type

Turn button

Tripping characteristic

Overload trigger: tripping class 10 A

Adjustment range undelayed short-circuit release - max

899 A

Adjustment range undelayed short-circuit release - min

899 A

Ambient operating temperature - max

55 °C

Ambient operating temperature - min

-25 °C

DA-CS-pkzm4

Sales notes

[eaton-link-module-for-motor-starters-pkz-flyer-fl034003en-en-us.pdf](#)

Specifications and datasheets

[Eaton Specification Sheet - 222394](#)

Wiring diagrams

[eaton-manual-motor-starters-starter-nzm-mccb-wiring-diagram.eps](#)

[eaton-manual-motor-starters-transformer-pkzm0-wiring-diagram.eps](#)

Ambient operating temperature (enclosed) - max

40 °C

Ambient operating temperature (enclosed) - min

-25 °C

Ambient storage temperature - max

80 °C

Ambient storage temperature - min

-40 °C

Assigned motor power at 230/240 V, 60 Hz, 1-phase

10 HP

Assigned motor power at 460/480 V, 60 Hz, 3-phase

40 HP

Assigned motor power at 575/600 V, 60 Hz, 3-phase

50 HP

Equipment heat dissipation, current-dependent P_{vid}

28.2 W

Heat dissipation capacity P_{diss}

0 W

Heat dissipation per pole, current-dependent P_{vid}

9.4 W

Internal resistance

2 mΩ

Rated impulse withstand voltage (U_{imp})

6000 V AC

Altitude

Max. 2000 m

Device construction

Built-in device fixed built-in technique

Explosion safety category for dust

ATEX dust-ex-protection, PTB 10, ATEX 3012, Ex II(2) G

Connection

Screw terminals

Electrical connection type of main circuit

Screw connection

Mounting position

Can be snapped on to IEC/EN 60715 top-hat rail with 7.5 or 15 mm height.

Lifespan, mechanical

30,000 Operations (Main conducting paths)

Overvoltage category

III

Degree of protection

IP20

Terminals: IP00

Number of poles

Three-pole

Lifespan, electrical

30,000 operations (at 400V, AC-3)

Shock resistance

15 g, Mechanical, According to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms

Functions

Motor protection

Phase failure sensitive

Terminal capacity (solid/stranded AWG)

14 - 2

Switching capacity

58 A (3 contacts in series), DC-5 up to 250V

58 A, AC-3 up to 690 V

Overload release current setting - max

58 A

Overload release current setting - min

50 A

Rated frequency - max

60 Hz

Rated frequency - min

50 Hz

Rated operational voltage (Ue) - max

690 V

Rated operational voltage (Ue) - min

690 V

Rated operational current for specified heat dissipation (In)

58 A

Rated operational power at AC-3, 220/230 V, 50 Hz

17 kW

Rated operational power at AC-3, 380/400 V, 50 Hz

30 kW

Rated uninterrupted current (I_u)

58 A

Static heat dissipation, non-current-dependent P_{vs}

0 W

Stripping length (main cable)

14 mm

Product category

Motor protective circuit breaker

Protection

Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)

Rated operational power at AC-3, 440 V, 50 Hz

37 kW

Rated operational power at AC-3, 500 V, 50 Hz

37 kW

Rated operational power at AC-3, 690 V, 50 Hz

55 kW

Rated short-circuit breaking capacity I_{cu} at 400 V AC

50 kA

Suitable for

Also motors with efficiency class IE3

Branch circuit: Manual type E if used with terminal, or suitable for group installations, (UL/CSA)

Short-circuit release

899 A, I_{rm}, Setting range max.

± 20% tolerance, Trip blocks

Basic device fixed 15.5 x I_u, Trip Blocks

Rated operational current (I_e)

58 A

Temperature compensation

-25 - 55 °C, Operating range

-5 - 40 °C to IEC/EN 60947, VDE 0660

≤ 0.25 %/K, residual error for T > 40°

Short-circuit current

60 kA DC, up to 250 V DC, Main conducting paths

Short-circuit current rating (group protection)

600 A, 600 V High Fault, max. Fuse, SCCR (UL/CSA)

42 kA, 600 V High Fault, Fuse, SCCR (UL/CSA)
42 kA, 600 V High Fault, CB, SCCR (UL/CSA)
600 A, 600 V High Fault, max. CB, SCCR (UL/CSA)

Short-circuit current rating (type E)

Accessories required BK50/3-PKZ4-E
50 kA, 480 Y/277 V, SCCR (UL/CSA)
50 kA, 240 V, SCCR (UL/CSA)

Tightening torque

3.3 Nm, Screw terminals, Main cable

Switch off technique

Thermomagnetic

Terminal capacity (flexible with ferrule)

1 x (0.75 - 35) mm², Main cables
2 x (0.75 - 25) mm², Main cables

Terminal capacity (solid)

1 x (0.75 - 16) mm², Main cables
2 x (0.75 - 16) mm²

Power loss

28.2 W



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia