

### product type designation



### CP 5711

Communications processor CP 5711 USB adapter (USB V2.0) for connection of a PG or Notebook to PROFIBUS or MPI; contain 2 m USB cable.

transfer rate	
transfer rate	
<ul style="list-style-type: none"> <li>at the 1st interface / according to PROFIBUS</li> </ul>	9.6 kbit/s ... 12 Mbit/s
interfaces	
number of electrical connections	
<ul style="list-style-type: none"> <li>at the 1st interface / according to PROFIBUS</li> </ul>	1
<ul style="list-style-type: none"> <li>for power supply</li> </ul>	1
number of interfaces / according to USB	1
type of electrical connection	
<ul style="list-style-type: none"> <li>at the 1st interface / according to PROFIBUS</li> </ul>	9-pin Sub-D socket (RS 485)
<ul style="list-style-type: none"> <li>for power supply</li> </ul>	2-pole terminal block
<ul style="list-style-type: none"> <li>of the USB interface</li> </ul>	Standard-B socket with mechanical interlock
standard for interfaces / USB 2.0	Yes
supply voltage, current consumption, power loss	
type of voltage / of the supply voltage	DC
type of voltage supply / optional external power supply	Yes
supply voltage	
<ul style="list-style-type: none"> <li>from USB</li> </ul>	5 V
<ul style="list-style-type: none"> <li>external</li> </ul>	24 V
<ul style="list-style-type: none"> <li>external</li> </ul>	18 ... 30 V
<ul style="list-style-type: none"> <li>note</li> </ul>	Supplied directly from USB provided that supply from PC is adequate; alternative external supply is possible
relative symmetrical tolerance / at DC	
<ul style="list-style-type: none"> <li>at 5 V</li> </ul>	5 %
<ul style="list-style-type: none"> <li>at 24 V</li> </ul>	5 %
consumed current	
<ul style="list-style-type: none"> <li>from USB</li> </ul>	0.5 A
<ul style="list-style-type: none"> <li>from external supply voltage / at DC / at 24 V / maximum</li> </ul>	0.3 A
power loss [W]	2.5 W
ambient conditions	
ambient temperature	
<ul style="list-style-type: none"> <li>during operation</li> </ul>	0 ... 60 °C
<ul style="list-style-type: none"> <li>during storage</li> </ul>	-40 ... +60 °C
<ul style="list-style-type: none"> <li>during transport</li> </ul>	-40 ... +60 °C
relative humidity / at 25 °C / without condensation / during operation / maximum	85 %
protection class IP	IP20
design, dimensions and weights	
module format	USB V2.0 adapter
width	85 mm

height	137 mm
depth	35 mm
net weight	300 g
fastening method	Mounting on DIN rail with optional mounting rail support
fastening method / 35 mm top hat DIN rail mounting	Yes
<b>product features, product functions, product components / general</b>	
number of plug-in cards of same design / plug-in / per PC station	1
number of units / note	-
<b>performance data / open communication</b>	
software / for open communication / by means of SEND/RECEIVE / required	Yes, SOFTNET-PB DP / SOFTNET-PB DP Slave / SOFTNET-PB S7
number of possible connections / for open communication / by means of SEND/RECEIVE / maximum	50
<b>performance data / PROFIBUS DP</b>	
software / for DP master function / required	Yes, SOFTNET-PB DP
service / as DP master	
• DPV0	Yes
• DPV1	No
• DPV2	No
number of DP slaves / on DP master / operable	64
data volume	
• of the address range of the inputs / as DP master / total	15616 byte
• of the address range of the outputs / as DP master / total	15616 byte
• of the address range of the inputs / per DP slave	244 byte
• of the address range of the outputs / per DP slave	244 byte
• of the address range of the diagnostic data / per DP slave	244 byte
software / for DP slave function / required	Yes, SOFTNET-PB DP slave
service / as DP slave	
• DPV0	Yes
• DPV1	No
data volume	
• of the address range of the inputs / as DP slave / total	122 byte
• of the address range of the outputs / as DP slave / total	122 byte
<b>performance data / S7 communication</b>	
software / for S7 communication / required	Yes, SOFTNET-PB S7
number of possible connections / for S7/PG communication / maximum	8
<b>performance data / multi-protocol mode</b>	
number of configurable connections / per PC station	207
<b>product functions / management, configuration, engineering</b>	
configuration software / required	Included in the scope of delivery of the required software product
<b>product functions / diagnostics</b>	
product function	
• port diagnostics	Yes
<b>standards, specifications, approvals</b>	
reference code	
• according to IEC 81346-2:2019	KEC
<b>accessories</b>	
accessories	optional: MPI cable, mounting rail support
<b>further information / internet links</b>	
internet link	
• to website: Selection guide for cables and connectors	<a href="https://support.industry.siemens.com/cs/ww/en/view/109766358">https://support.industry.siemens.com/cs/ww/en/view/109766358</a>
• to web page: selection aid TIA Selection Tool	<a href="https://www.siemens.com/tstcloud">https://www.siemens.com/tstcloud</a>
• to website: Industrial communication	<a href="https://www.siemens.com/simatic-net">https://www.siemens.com/simatic-net</a>
• to web page: SiePortal	<a href="https://sieportal.siemens.com/">https://sieportal.siemens.com/</a>
• to website: Image database	<a href="https://www.automation.siemens.com/bilddb">https://www.automation.siemens.com/bilddb</a>
• to website: CAX-Download-Manager	<a href="https://www.siemens.com/cax">https://www.siemens.com/cax</a>
• to website: Industry Online Support	<a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>
<b>security information</b>	
security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks

In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit [www.siemens.com/cybersecurity-industry](https://www.siemens.com/cybersecurity-industry). Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under <https://www.siemens.com/cert>. (V4.7)

Approvals / Certificates

General Product Approval



[Declaration of Con-  
formity](#)



General Product Ap- proval	EMV	For use in hazardous locations		Environment
-------------------------------	-----	--------------------------------	--	-------------



[KC](#)



[CCC-Ex](#)

[Confirmation](#)

Environment



last modified:

8/8/2024