

# Specifications



## Eaton 167113

Eaton Moeller series xEffect - FRCmM-NA  
RCCB. Residual current circuit breaker (RCCB),  
25A, 2p, 30mA, type A, UL

### General specifications

|                      |   |
|----------------------|---|
| PRODUCT NAME         | Eaton Moeller series xEffect - FRCmM-NA RCCB  |
| CATALOG NUMBER       | 167113  |
| MODEL CODE           | FRCMM-25/2/003-A-NA   |
| EAN                  | 4015081636150   |
| PRODUCT LENGTH/DEPTH | 76 mm   |
| PRODUCT HEIGHT       | 80 mm   |
| PRODUCT WIDTH        | 35 mm   |
| PRODUCT WEIGHT       | 0.22 kg   |
| COMPLIANCES          | RoHS conform  |
| CERTIFICATIONS       | UL 1053<br>IEC/EN 61008<br>EN45545-2<br>IEC 61373                                     |
| CATALOG NOTES        | Protects against special forms of residual pulsating DC which have not been smoothed. |



Powering Business Worldwide

## Product specifications

|   |  |
|---|--|
| <b>USED WITH</b>  | Type A<br>Residual current circuit breakers<br>FRCmM-NA  |
| <b>TYPE</b>   | <ul style="list-style-type: none"> <li>FRCmM-NA</li> <li>Residual current circuit breakers</li> <li>Type A</li> </ul>  |
| <b>SPECIAL FEATURES</b>   | <ul style="list-style-type: none"> <li>Current test marks as per inscription</li> <li>Maximum operating temperature is 55 °C: Starting at 40 °C, the max. permissible continuous current decreases by 3% for every 1 °C</li> <li>The maximum operating current of back-up fuse must not exceed the residual current circuit breaker's rated operational current</li> </ul> |
| <b>APPLICATION</b>  | Switchgear for export to North America (UL-listed)   |
| <b>AMPERAGE RATING</b>  | 25 A   |
| <b>FEATURES</b>   | Additional equipment possible<br><br>Residual current circuit breaker  |
| <b>10.10 TEMPERATURE RISE</b>   | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.   |
| <b>10.11 SHORT-CIRCUIT RATING</b>   | Is the panel builder's responsibility. The specifications for the switchgear must be observed.   |
| <b>10.12 ELECTROMAGNETIC COMPATIBILITY</b>  | Is the panel builder's responsibility. The specifications for the switchgear must be observed.   |
| <b>10.13 MECHANICAL FUNCTION</b>  | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.   |
| <b>10.2.2 CORROSION RESISTANCE</b>  | Meets the product standard's requirements.   |
| <b>10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES</b>                   | Meets the product standard's requirements.   |
| <b>10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT</b> | Meets the product standard's requirements.   |
| <b>10.2.3.3 RESIST. OF INSUL.</b>   | Meets the product standard's   |

## Resources

|                                      |  |
|--------------------------------------|--|
| <b>APPLICATION NOTES</b>             | <a href="#">eaton-rcd-application-guide-br019003en-en-us.pdf</a>   |
| <b>CATALOGS</b>                      | <a href="#">eaton-xeffect-frcmm-na-rccb-catalog-ca003019en-en-us.pdf</a><br><br><a href="#">Circuit Protection, Miniature Circuit Breakers and Supplementary Protectors, Volume 4, Tab 1</a><br><br><a href="#">eaton-xeffect-industrial-switchgear-range-catalog-ca003002en-en-us.pdf</a> |
| <b>DECLARATIONS OF CONFORMITY</b>    | <a href="#">03_FRCm-NA_181019</a><br><br><a href="#">DA-DC-03_FRCm</a>   |
| <b>DRAWINGS</b>                      | <a href="#">eaton-circuit-breaker-xeffect-frcmm-na-rccb-dimensions.eps</a>   |
| <b>ECAD MODEL</b>                    | <a href="#">ETN.FRCMM-25_2_003-A-NA</a>  |
| <b>INSTALLATION INSTRUCTIONS</b>     | <a href="#">MA180503312</a>  |
| <b>MCAD MODEL</b>                    | <a href="#">eaton-residual-current-circuit-breakers-3d-models-f9-ul1053-2p.stp</a><br><br><a href="#">eaton-residual-current-circuit-breakers-drawings-f9-ul1053-2p.dwg</a>  |
| <b>SPECIFICATIONS AND DATASHEETS</b> | <a href="#">Eaton Specification Sheet - 167113</a>   |
| <b>WIRING DIAGRAMS</b>               | <a href="#">eaton-xeffect-frcmm-rccb-wiring-diagram.jpg</a><br><br><a href="#">eaton-circuit-breaker-xeffect-frcmm-na-rccb-wiring-diagram.eps</a>  |

|   |   |
|---|---|
| <b>MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS</b>    | requirements.   |
| <b>10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION</b>         | Meets the product standard's requirements.                                    |
| <b>10.2.5 LIFTING</b>   | Does not apply, since the entire switchgear needs to be evaluated.            |
| <b>10.2.6 MECHANICAL IMPACT</b>                                 | Does not apply, since the entire switchgear needs to be evaluated.            |
| <b>10.2.7 INSCRIPTIONS</b>                                      | Meets the product standard's requirements.                                    |
| <b>10.3 DEGREE OF PROTECTION OF ASSEMBLIES</b>                  | Does not apply, since the entire switchgear needs to be evaluated.            |
| <b>10.4 CLEARANCES AND CREEPAGE DISTANCES</b>                   | Meets the product standard's requirements.                                    |
| <b>10.5 PROTECTION AGAINST ELECTRIC SHOCK</b>                   | Does not apply, since the entire switchgear needs to be evaluated.            |
| <b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>   | Does not apply, since the entire switchgear needs to be evaluated.            |
| <b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>        | Is the panel builder's responsibility.  |
| <b>10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS</b>                 | Is the panel builder's responsibility.  |
| <b>10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH</b>                 | Is the panel builder's responsibility.  |
| <b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>                         | Is the panel builder's responsibility.  |
| <b>10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL</b> | Is the panel builder's responsibility.  |
| <b>FITTED WITH:</b>   | Interlocking device   |
| <b>FRAME</b>  | 45 mm   |
| <b>FREQUENCY RATING</b>   | 50 Hz / 60 Hz   |
| <b>POLLUTION DEGREE</b>   | 2   |
| <b>MOUNTING METHOD</b>  | Quick attachment with 2 latch positions for DIN-rail IEC/EN 60715<br>DIN rail |
| <b>CLIMATIC PROOFING</b>  | 25-55 °C / 90-95% relative humidity according to IEC 60068-2                  |
| <b>EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT</b>            | 2 W   |
| <b>RATED IMPULSE WITHSTAND VOLTAGE (UIMP)</b>                   | 4 kV  |
| <b>RATED SHORT-TIME WITHSTAND CURRENT (ICW)</b>                 | 10 kA   |

|  |  |
|--|--|
| <b>ADMISSIBLE BACK-UP FUSE OVERLOAD - MAX</b>                  | 25 A gG/gL   |
| <b>AMBIENT HUMDITY RANGE</b>                                   | 5 - 95 %   |
| <b>BUILT-IN WIDTH (NUMBER OF UNITS)</b>                        | 35 mm (2 SU)   |
| <b>SHORT-CIRCUIT RATING</b>                                    | Max. admissible back-up fuse: 63 A gG/gL, 70 A class J fuse (UL) |
| <b>STATUS INDICATION</b>                                       | White / blue   |
| <b>TERMINAL PROTECTION</b>                                     | Finger and hand touch safe, DGUV VS3, EN 50274                   |
| <b>TERMINALS (TOP AND BOTTOM)</b>                              | Lift terminals   |
| <b>TEST CIRCUIT RANGE</b>                                      | 184 V AC - 440 V AC, 196 V AC - 305 V AC (UL)                    |
| <b>AMBIENT OPERATING TEMPERATURE - MAX</b>                     | 40 °C  |
| <b>AMBIENT OPERATING TEMPERATURE - MIN</b>                     | -25 °C   |
| <b>BUILT-IN DEPTH</b>  | 70.5 mm  |
| <b>CONNECTABLE CONDUCTOR CROSS SECTION (MULTI-WIRED) - MAX</b> | 16 mm <sup>2</sup>   |
| <b>CONNECTABLE CONDUCTOR CROSS SECTION (MULTI-WIRED) - MIN</b> | 1.5 mm <sup>2</sup>  |
| <b>CONNECTABLE CONDUCTOR CROSS SECTION (SOLID-CORE) - MAX</b>  | 35 mm <sup>2</sup>   |
| <b>CONNECTABLE CONDUCTOR CROSS SECTION (SOLID-CORE) - MIN</b>  | 1.5 mm <sup>2</sup>  |
| <b>FAULT CURRENT RATING</b>                                    | 30 mA  |
| <b>HEAT DISSIPATION CAPACITY</b>                               | 0 W  |
| <b>HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT</b>            | 1 W  |
| <b>OVERVOLTAGE TESTED - MAX</b>                                | 530 V  |
| <b>PERMITTED STORAGE AND TRANSPORT TEMPERATURE - MAX</b>       | 60 °C  |
| <b>PERMITTED STORAGE AND TRANSPORT TEMPERATURE - MIN</b>       | -35 °C   |
| <b>CONTACT POSITION INDICATOR COLOR</b>                        | Red / green  |
| <b>MOUNTING POSITION</b>                                       | As required  |
| <b>LIFESPAN, MECHANICAL</b>                                    | 10000 operations   |
| <b>DEGREE OF PROTECTION</b>                                    | IP20, IP40 with suitable enclosure<br>IP20                       |

|  |  |
|--|--|
| <b>IMPULSE WITHSTAND CURRENT</b>                                     | 250 A (8/20 µs) surge-proof<br>Partly surge-proof 250 A          |
| <b>NUMBER OF POLES</b>   | Two-pole   |
| <b>LEAKAGE CURRENT TYPE</b>  | A  |
| <b>LIFESPAN, ELECTRICAL</b>  | 4000 operations  |
| <b>PICK-UP CURRENT</b>   | 22 mA  |
| <b>SENSITIVITY TYPE</b>  | Pulse-current sensitive  |
| <b>TERMINAL CAPACITY (CABLE)</b>                                     | M5 (with cross-recessed screw as defined in EN ISO 4757-Z2, PZ2) |
| <b>RATED FAULT CURRENT - MAX</b>                                     | 0.03 A   |
| <b>RATED FAULT CURRENT - MIN</b>                                     | 0.03 A   |
| <b>RATED INSULATION VOLTAGE (UI)</b>                                 | 440 V  |
| <b>RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)</b> | 25 A   |
| <b>RATED OPERATIONAL VOLTAGE (UE) - MAX</b>                          | 277 V  |
| <b>RATED RESIDUAL MAKING AND BREAKING CAPACITY</b>                   | 500 A  |
| <b>STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT</b>                | 0 W  |
| <b>SURGE CURRENT CAPACITY</b>  | 0.25 kA  |
| <b>WIDTH IN NUMBER OF MODULAR SPACINGS</b>                           | 2  |
| <b>VOLTAGE RATING (IEC/EN 60947-2)</b>                               | 240 V AC / 415 V AC  |
| <b>VOLTAGE RATING (UL)</b>   | 480Y/277 V, 60 Hz  |
| <b>VOLTAGE TYPE</b>  | AC   |
| <b>TERMINAL CAPACITY (SOLID WIRE)</b>                                | 1.5 mm <sup>2</sup> - 35 mm <sup>2</sup>                         |
| <b>TRIPPING TIME</b>   | Non-delayed  |
| <b>RATED SHORT-CIRCUIT STRENGTH</b>                                  | 5 kA (UL, as per CSA)<br>10 kA with back-up fuse                 |
| <b>TERMINAL CAPACITY (STRANDED CABLE)</b>                            | 16 mm <sup>2</sup> (2x)  |
| <b>RAL-NUMBER</b>  | 7035   |
| <b>COLOR</b>   | Gray   |

|                 |
|-----------------|
| PROJECT NAME:   |
| PROJECT NUMBER: |
| PREPARED BY:    |
| DATE:           |



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

Follow us on social media to get the latest product and support information.

