

Specifications



Eaton KTK-R-4

Eaton Bussmann Series Class CC fuse, KTK-R, fast-acting, dual-element current limiting fuse, 4 A, rejection style fuse, interrupting rating of 200kA at 600Vac

General specifications

PRODUCT NAME	Eaton Bussmann series KTK-R fuse
CATALOG NUMBER	KTK-R-4
UPC	051712420631
EAN	5027590445672
PRODUCT LENGTH/DEPTH	1.5 in
PRODUCT HEIGHT	0.41 in
PRODUCT WIDTH	0.41 in
PRODUCT WEIGHT	0.015 lb
WARRANTY	Not Applicable
COMPLIANCES	RoHS Compliant CE Marked
CERTIFICATIONS	UL Listed CSA Certified

Product specifications

TYPE	Current-limiting fast-acting fuse
SPECIAL FEATURES	Rejection style
APPLICATION	Industrial controls panels and machinery, street lighting, general lighting, capacitors and distribution
AMPERAGE RATING	4 A
NUMBER OF ELEMENTS	Dual
CLASS	Class CC
INTERRUPT RATING	200 kAIC
FUSE INDICATOR	Non-indicating
CONNECTION	Ferrule end x ferrule end Ferrule
RESPONSE TIME	See time current curve
MATERIAL	Melamine tube
PACKAGING TYPE	Standard
QUANTITY	10
VOLTAGE RATING	600 V

Resources

	Bussmann Full Line Catalog
	Low Voltage Branch Circuit Fuse Chapter
CATALOGS	Bussmann series complete full line catalog no. 1007
CERTIFICATION REPORTS	Eaton Bussmann EU Declaration of conformity 93-68-EEC2000
DRAWINGS	DA-PD-Bus Ele DS 1015 KTK-R
MULTIMEDIA	Bussmann series Fuseology
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - KTK-R-4
TECHNICAL DATA SHEETS	KTK-R Spec Sheet KTK-R-4~CLASS CC FAST ACTING FUSE CLASS CC

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. All Rights Reserved.