

Siemens
EcoTech



LOGO! 24RCE, logic module, display power supply / I/O: 24 V AC/24 V DC/relay, 8 DI/4 DO, memory 400 blocks, modularly expandable, Ethernet, integrated web server, data log, user-defined web pages, standard microSD card for LOGO! Soft Comfort V8.4 or higher, older projects executable cloud connection, MQTT in all LOGO! 8.4 basic units



Figure similar

Display	
with display	Yes
Installation type/mounting	
Mounting	on 35 mm DIN rail, 4 spacing units wide
Supply voltage	
Rated value (DC)	
• 24 V DC	Yes
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Rated value (AC)	
• 24 V AC	Yes
Line frequency	
• permissible range, lower limit	47 Hz
• permissible range, upper limit	63 Hz
Time of day	
Time switching clocks	
• Number	400; Max. 400, function-specific
• Power reserve	480 h
Digital inputs	
Number of digital inputs	8
Digital outputs	
Number of digital outputs	4; Relays
Short-circuit protection	No; external fusing necessary
Relay outputs	
Switching capacity of contacts	
— with inductive load, max.	3 A
— with resistive load, max.	10 A
EMC	
Emission of radio interference acc. to EN 55 011	
• Limit class B, for use in residential areas	Yes; Radio interference suppression according to EN55011, Limit Value Class B
Standards, approvals, certificates	
Siemens Eco Profile (SEP)	Siemens EcoTech
CE mark	Yes
CSA approval	No; covered by UL cert
UL approval	Yes

FM approval	Yes																																	
developed in accordance with IEC 61131	Yes																																	
according to VDE 0631	Yes																																	
Marine approval	Yes; in preparation																																	
Ecological footprint																																		
• environmental product declaration	Yes																																	
Global warming potential																																		
— global warming potential, (total) [CO2 eq]	51.5 kg																																	
— global warming potential, (during production) [CO2 eq]	9.64 kg																																	
— global warming potential, (during operation) [CO2 eq]	42.1 kg																																	
— global warming potential, (after end of life cycle) [CO2 eq]	-0.364 kg																																	
Ambient conditions																																		
Ambient temperature during operation																																		
• min.	-20 °C; No condensation																																	
• max.	55 °C																																	
Ambient temperature during storage/transportation																																		
• min.	-40 °C																																	
• max.	70 °C																																	
Altitude during operation relating to sea level																																		
• Ambient air temperature-barometric pressure-altitude	Tmin ... Tmax at 1 080 hPa ... 795 hPa (-1 000 m ... +2 000 m)																																	
Dimensions																																		
Width	71.5 mm																																	
Height	90 mm																																	
Depth	60 mm																																	
Classifications																																		
	<table><tr><th></th><th>Version</th><th>Classification</th></tr><tr><td>eClass</td><td>14</td><td>27-24-22-16</td></tr><tr><td>eClass</td><td>12</td><td>27-24-22-16</td></tr><tr><td>eClass</td><td>9.1</td><td>27-24-22-16</td></tr><tr><td>eClass</td><td>9</td><td>27-24-22-16</td></tr><tr><td>eClass</td><td>8</td><td>27-24-22-16</td></tr><tr><td>eClass</td><td>7.1</td><td>27-24-22-16</td></tr><tr><td>eClass</td><td>6</td><td>27-24-22-16</td></tr><tr><td>ETIM</td><td>9</td><td>EC001417</td></tr><tr><td>ETIM</td><td>8</td><td>EC001417</td></tr><tr><td>ETIM</td><td>7</td><td>EC001417</td></tr></table>		Version	Classification	eClass	14	27-24-22-16	eClass	12	27-24-22-16	eClass	9.1	27-24-22-16	eClass	9	27-24-22-16	eClass	8	27-24-22-16	eClass	7.1	27-24-22-16	eClass	6	27-24-22-16	ETIM	9	EC001417	ETIM	8	EC001417	ETIM	7	EC001417
	Version	Classification																																
eClass	14	27-24-22-16																																
eClass	12	27-24-22-16																																
eClass	9.1	27-24-22-16																																
eClass	9	27-24-22-16																																
eClass	8	27-24-22-16																																
eClass	7.1	27-24-22-16																																
eClass	6	27-24-22-16																																
ETIM	9	EC001417																																
ETIM	8	EC001417																																
ETIM	7	EC001417																																
Approvals / Certificates																																		
<table><tr><td>General Product Approval</td><td>For use in hazardous locations</td></tr></table>		General Product Approval	For use in hazardous locations																															
General Product Approval	For use in hazardous locations																																	
 EG-Konf.   UL  RCM KC  CQC																																		
<table><tr><td>For use in hazardous locations</td><td>Maritime application</td></tr></table>		For use in hazardous locations	Maritime application																															
For use in hazardous locations	Maritime application																																	
FM  ABS  BUREAU VERITAS  DNV  LRS NK / Nippon Kaiji Kyokai																																		
Maritime application	Environment																																	

last modified:

5/16/2025 