

Thermo-elektris. ontvochtiger, 24 VDC

CATALOGUSNUMMER

H2OMITTER



De H2Omit thermo-elektrische ontvochtiger verwijdt vocht uit de lucht in een behuizing en biedt een goedkope en zeer effectieve manier om elektronische en elektrische componenten te beschermen tegen condensatie.

INDUSTRIENORMEN

UL 508A Listed; File No. E61997

cUL Listed per C22.2 No. 14; File No. E61997

CE

KENMERKEN

Vermindert corrosie die de levensduur van interne elektrische en elektronische componenten kan beperken

Draaiende ventilatieopeningen aan de zijkant leiden de recirculatielucht weg van de kritische bedieningselementen

Un tuyau en plastique de 1,3 m

Condenses moisture from internal enclosure air and standing liquids

Built-in drain provision with plastic hose directs collected moisture to the Vent Drain (sold separately)

Mounts via DIN rail on internal panel or mounts directly onto the inside bottom of enclosure above the Vent Drain (sold separately)

Can be used in mild steel, aluminum, stainless steel and non-metallic enclosures

High-impact ABS shell

Operates on 24-Volt DC power

4.5 A max. (84 W)

Runs continuously above 32 F (power supply not included) *

Removes 8 oz. of moisture in 24 hours

Compact 6.00 x 5.50 x 5.75-inch design

One Thermoelectric Dehumidifier includes

Two hose retainers

One double-ended hose retainer

Six inches of Velcro®

Seven-inch strip of DIN rail

Two mounting screws

PRODUCTKENMERKEN

Breedte: 140mm

Diepte: 146mm

Materiaal: ABS

Afwerking: Glad mat

Kleur: Grijs

Diepte: 146mm

Hoogte: 152mm

AANVULLENDE PRODUCTGEGEVENS

* If continual operation is not desired, a Mechanical Hygrostat (AMHUM) can be wired to the thermoelectric dehumidifier and then set to turn the dehumidifier on at the desired relative humidity.

VELCRO is a trademark of Velcro Industries B.V.

WAARSCHUWING

nVent-producten moeten alleen worden geïnstalleerd en gebruikt zoals aangegeven in de instructiebladen en trainingsmateriaal van nVent. Instructiebladen zijn beschikbaar op www.nvent.com en bij uw nVent klantenservicevertegenwoordiger. Onjuiste installatie, misbruik, verkeerde toepassing of ander falen om de instructies en waarschuwingen van nVent volledig te volgen, kan leiden tot productstoringen, schade aan eigendommen, ernstig lichamelijk letsel en de dood en/of uw garantie ongeldig maken.



Ons krachtige merkenportfolio:

CADDY

ERICO

HOFFMAN

ILSCO

SCHROFF

TRACHTE