

### product type designation



### Cu/FO Modular Outlet

Cu/FO modular outlet module support for mounting of IE RJ45 Keystone or FO LC coupler; mounting on DIN rail; 1 pack = 1 unit.

### suitability for use

Module carrier for mounting up to 6 IE RJ45 Keystone (6GK19010BE100AA0) and / or FO LC Coupler (6GK19010RP100AA0) on a DIN rail

### mechanical data

material / of the enclosure	metal
-----------------------------	-------

### design, dimensions and weights

width	61 mm
height	132 mm
depth	132 mm
net weight	685 g
fastening method	
• 35 mm top hat DIN rail mounting	Yes

### ambient conditions

ambient temperature	
• during operation	-40 ... +70 °C
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
protection class IP	IP20

### product features, product functions, product components / general

product feature	
• silicon-free	Yes
product component / strain relief	Yes

### standards, specifications, approvals

certificate of suitability	
• RoHS conformity	Yes

### further information / internet-Links

Internet-Link	
• to website: Industrial communication	<a href="http://www.siemens.com/simatic-net">http://www.siemens.com/simatic-net</a>
• to website: Industry Mall	<a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a>
• to website: Information and Download Center	<a href="http://www.siemens.com/industry/infocenter">http://www.siemens.com/industry/infocenter</a>
• to website: Selection guide for cables and connectors	<a href="https://sie.ag/2QdlxcP">https://sie.ag/2QdlxcP</a>
• to website: Image database	<a href="http://automation.siemens.com/bilddb">http://automation.siemens.com/bilddb</a>
• to website: CAx-Download-Manager	<a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a>
• to website: Industry Online Support	<a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>

### last modified:

8/26/2021

