

### product type designation



### IE FC RJ45 modular outlet (without insert)

IE FC RJ45 modular outlet Base module without insert CAT6 1 pack = 1 unit.

transfer rate	
transfer rate	
• 1 / for Industrial Ethernet	10 Mbit/s
• 2 / for Industrial Ethernet	100 Mbit/s
• 3 / for Industrial Ethernet	1000 Mbit/s
interfaces	
number of electrical connections	
• for Industrial Ethernet FC TP cables	1
type of electrical connection	
• for Industrial Ethernet FC TP cables	integrated insulation displacement contacts
• FastConnect	Yes
mechanical data	
material / of the enclosure	metal
number of reuses	10
design, dimensions and weights	
width	50 mm
height	115.25 mm
depth	58.95 mm
net weight	450 g
connectable cable cross-section	9.5 ... 9.5
fastening method	
• 35 mm top hat DIN rail mounting	Yes
• wall mounting	Yes
ambient conditions	
ambient temperature	
• during operation	-20 ... +70 °C
• during storage	-40 ... +80 °C
• during transport	-40 ... +80 °C
relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
protection class IP	IP40
product features, product functions, product components / general	
product feature	
• silicon-free	Yes
standards, specifications, approvals	
certificate of suitability	
• RoHS conformity	Yes
• UL approval	Yes

standard for structured cabling	Cat 6
further information / internet-Links	
Internet-Link	
<ul style="list-style-type: none"> <li>• to website: Industrial communication</li> <li>• to website: Industry Mall</li> <li>• to website: Information and Download Center</li> <li>• to website: Selection guide for cables and connectors</li> <li>• to website: Image database</li> <li>• to website: CAX-Download-Manager</li> <li>• to website: Industry Online Support</li> </ul>	<a href="http://www.siemens.com/simatic-net">http://www.siemens.com/simatic-net</a> <a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a> <a href="http://www.siemens.com/industry/infocenter">http://www.siemens.com/industry/infocenter</a> <a href="https://sie.ag/2QdlxcP">https://sie.ag/2QdlxcP</a>  <a href="http://automation.siemens.com/bilddb">http://automation.siemens.com/bilddb</a> <a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a> <a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>
last modified:	6/30/2021 