



H2 Lite T

Dimmable, fire-rated LED downlight complete with bezel and terminal connector



Suitable for use in bathrooms



Push-fit terminal connector included



Insulation coverable



High efficacy



4-year extended warranty available



* IP65 (front) / IP20 (back) | * Ceiling only | Patent information: collingwoodlighting.com/patent

PHOTOMETRICS @ 25°C

Colour	Beam angle	Finish	Product code	CRI	lm	lm/W	lx at 1m
4000K	55°	B / steel	DLT388BS5540	>80Ra	460	105	527
	55°	Matt white	DLT388MW5540	>80Ra	460	105	527
3000K	55°	B / steel	DLT388BS5530	>80Ra	440	100	504
	55°	Matt white	DLT388MW5530	>80Ra	440	100	504

GENERAL

Building regulations	Part B (fire protection), C (moisture protection), E (acoustic protection), P (electrical safety) and L (conservation of energy - 2014 regulations)
Construction material	Mild steel / VO rated plastic insulation protector built in
Flicker free	Yes
Inrush current	1A 0.25ms
Maximum ceiling thickness	40mm

WIRING

Cable / flying lead	0.15m (Class II)
Cable required for 'T' Connector	Push-fit terminal for: Twin & Earth (6242Y 2x1.5mm²) or 3-core cable (R02V 3x1.5mm²)
Type of wiring required	Parallel (mains) 220-240V AC 50/60Hz

LED DRIVERS


Product code	Input voltage	Input current	Power factor	Dimming	Bathroom zone
N/A (integrated SELV driver)	220-240V	-	>0.8	Yes (mains)	1 (ceiling only)

ACCESSORIES

Product code	Description	
DLCONVERT70	Converter plate	88
DM298GRID	LED mains grid dimmer	89
DM298FP	Faceplate dimmer	89

FEATURES & BENEFITS

- > 100lm/W+
- > Insulation coverable
- > Only 4.4W
- > Uses single point source technology to replicate traditional halogen look
- > Mains dimmable
- > Compact integral driver for easy installation
- > Push-fit terminal connector included
- > LED downlight complete with bezel for a straightforward fit



4000K 55°

Additional diagrams available at collingwoodlighting.com

