

# ROBUS Socket Duplicator

## RKC2S

**Please read instructions before commencing installation and retain for future reference.**

### Specification:



Bakelite resin twin switched 13A BS1363 socket outlet intended for mounting on recessed 1 gang boxes to convert 1 gang socket outlet to 2 gang socket without modification to existing wiring or building structure.

Dimensions:      Width: 146mm  
                      Height: 86mm  
Projection:        22mm  
Weight: (Kg)       Nett: 0.170  
Supply:              230/240V 50Hz  
Terminal:            2 x 6mm<sup>2</sup> max  
Fixing screws:      2 off M3.5x 30

Complies with BS1363

### Installation:

**!Electrical products can cause death or injury, or damage to property. If in any doubt about the installation or use of this product, consult a competent electrician. This fitting is designed for surface mounting on walls where a 1 gang recessed box (or dry lining box) is already installed.**

- 1 Ensure mains supply is switched off
- 2 Remove unit fixing screws and their square caps from storage at back of Duplicator unit
- 3 Remove existing 1 gang socket from wall, taking note of wiring connections
- 4 Connect existing wires to same marked terminals L, N and earth on Duplicator unit
- 5 Fix Duplicator to back box securely with screws provided
- 6 Fit square caps to cover fixing screws

Duplicator unit is now ready for use.

• The installation must be carried out by an electrician. •