



2kW 5L Oversink Vented Water Heater

NLVOS5L

Description

Simple to install traditional vented oversink water heater for a single sink. Slimline design supplied complete with tap and spout.

Ideal for occasional light use dishwashing at a single kitchen sink in the workplace, for example, portable buildings, offices, shops, workshops, garages and other small commercial premises.

Key features

- Complete with tap and spout (must be used)
- White corrosion proof case for durability
- Cable pre-wired saves time on installation
- No need for expansion vessel, relief or reducing valve
- Frost protection setting
- Safety resettable thermal cut out - simply switch off to reset

Technical details

Tank Capacity
5L

Tank Material
Polypropylene

Tank Insulation Material
Polystyrene

Dimensions (H x W x D)
400 x 270 x 180 (mm)

Weight (empty)
3.5kg

Weight (full)
8.5kg

Thermal-Cut-Out
Auto reset

Thermostat
Bulb type - adjustable up to 80degrees

Heating Element
Copper - Screw fit

Connections
1/2" MBSP to cold side

Fittings Required
Chrome spout - provided
Inlet tap - provided

Supplied power cable length
1m

Newlec[®] Technical Data Sheet

Heat up time TO 75 (AMBIENT 10°C)
approx 12 mins

Application

Suitable for a single sink only. Users with a requirement to serve more than 1 sink or to use regular taps should consider an unvented water heater (e.g. NL10LUWH).

Wall Fixing Bracket

Included for fast installation

IP Rating IP24

Standard Warranty

12 months

Approvals

CE

Date completed by manufacturer:

19/1/15