

MODE

SPECIFICATION SHEET

Product Code

CMA649

Description

3A Fused Connection Unit





General Information	
Dimensions	86mm x 86mm x 9.5mm
Material composition	Rear Housing: Nylon
	Front Plate: Urea
	Terminals: Brass
	Earth Strap: Mild Steel
	Terminal Screws: Steel and Yellow Passivated
	Silver "on-lay" copper/brass contacts
Back Box Depth	25mm – 47mm
Cable Size	4 x 2.5mm ²
Terminal Size	Live: 5mm
	Neutral: 5mm
	Earth: 5mm
Switched	No
Double Pole	No
Twin Earth	Yes
Fuse Size	3A
Flex Outlet	No
Neon	No
Warranty	20 Years Domestic

Standards	BS 1363
	BS 1362 (Fuse)

A al al : 4 : a . a . a . l	Indiana attan
Additional	Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram supplied with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases. All products independently tested achieved a 99.9% kill rate across all four types of the strains of bacteria – MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.

V1.0