

SPECIFICATION SHEET

Product Code DB750

Description 100A Fused Main Switch



General Information				
Dimensions	133mm x 101mm x 60mm (70mm with switch)			
Material composition	Housing: Urea Base: Steel Contacts: Copper Terminals: Brass			
Terminal Size	Live: 9mm Neutral: 9mm Earth: 7.5mm			
Torque Value	2.5Nm			
Cable Size	1 x 35mm ² (Live & Neutral) 1 x 25mm ² (Earth)			
Rating	100A Max			
Fuse Included	80A HRC			
Locking Facility	No			
Warranty	5 Years Domestic			
Other Information				
Standards	BS 60947-03			
Extra Information	DB981 Elongated Cable Shroud available & DB791 Metal Enclosure available to comply with Amendment 3. Termination of armoured cable must be carried out the correct cable gland. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram supplied with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. 80A and 100A variants are supplied with an 80A Bussmann fuse as standard. However the fuses in the table below will fit			
	Fuse Manufacturer			
Rating	Bussmann	Lawson	MEM	GE
40A	40KR85	ME40	404R	RHF40
45A	45KR85	ME45	454R	-
50A	50KR85	ME50	504R	RHF50
60A	60KR85	ME60	604R	RHF60
70A	70KR85	ME70	-	-
80A	80KR85	ME80	804R	RHF80
100A	100KR85	ME100	-	-

Errors & Omissions excluded. Specification is subject to change without notice.

V1.0