

## MODE

## **SPECIFICATION SHEET**

Product Code CMA017 Description 20A Flex Outlet Plate





| General Information  |  |
|----------------------|--|
| Dimensions           | 86mm x 86mm x 9.5mm                            |
| Material composition | Front Plate: Urea                              |
|                      | Terminals: Brass                               |
|                      | Earth Strap: Mild Steel                        |
|                      | Terminal Screws: Steel and Yellow Passivated   |
|                      | Silver "on-lay" copper/brass contacts.         |
| Back Box Depth       | 16mm – 47mm                                    |
| Cable Size           | 4 x 2.5mm <sup>2</sup> or 1 x 6mm <sup>2</sup> |
| Terminal Size        | Live: 5mm                                      |
|                      | Neutral: 5mm                                   |
|                      | Earth: 5mm                                     |
| Twin Earth           | Yes  |
| Flex Outlet          | Yes (Centre of Plate or Through The Bottom)    |
| Neon                 | No   |
| Warranty             | 20 Years Domestic                              |

| Standards | BS 5733 |
|-----------|---------|
|           |         |

| Additional Information | Ensure that the mains supply is isolated before commencing installation      |
|------------------------|--|
|                        | and refer to the circuit diagram supplied with the relevant product.         |
|                        | Bare earth cables must always be covered with appropriate sleeving and       |
|                        | wired to the earth terminal.   |
|                        | All white moulded accessories are manufactured using Urea                    |
|                        | Formaldehyde, which has similar inherent properties to antimicrobial         |
|                        | additives that inhibit the growth of infectious diseases. All products       |
|                        | independently tested achieved a 99.9% kill rate across all four types of the |
|                        | strains of bacteria – MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae    |
|                        | Flex Outlet Diameter: 10mm   |

V1.0