

Product Datasheet model i-vo 9160 520



**UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189,
D-90766 Fürth**

Product characteristics	* Duo-spherical lens * Duo component technology * Extremely comfortable for all-day wear * Shock absorbing brow guard * Indirect ventilation * Quattroflex patented temple * Adjustable temple length and lens inclination
Technical details Frame Material Colour Material Features Colour	Front piece TPU/TPE blue/orange Side piece PA 5 position length adjustability blue

Material	Temple
Features	PBT+PC/TPE
Colour	quattroflex temple blue/orange
	Marking
Manufacturer's ID code	W
Applicable EN norm	166
Low-energy impact	F (45 m/s)
Resistance to high speed particles at extremes of temperat.	T
Conformity symbol	CE
No. of certificat.body	0196
Lens	
Material	PC
Thickness	3 mm
Coating	uvex supravision sapphire
Colour	amber
	Marking
Filter	2C-1,2 (DIN EN 170)
Manufacturer's ID code	W
Optical class	1
Low-energy impact	F (45 m/s)
Resistance to high speed particles at extremes of temperat.	T
Surface resistance to fine particles	K
Antifog	N
Conformity symbol	CE

Miscellaneous	
Weight	33 g
Packing	5 spectacles per box 200 spectacles per cardboard box
Standards	DIN EN 166 + DIN EN 170