



SPECIFICATION SHEET


Product Code

FP*411#

Description

'Ingot' 10AX 1 Gang 2 Way Switch





General Information	
Dimensions	88mm x 88mm x 1.3mm (Excluding Gasket)
Finishes Available	Replace * with: BS (Brushed Steel), BN (Black Nickel), PN (Pearl Nickel),
	CH (Polished Chrome), SS (Stainless Steel)
Inserts Available	Replace # with: WH (White), and BK (Black).
	(Black Nickel finishes are supplied with black insert)
Material Composition	Rear Housing: Nylon
	Front Plate: Stainless Steel
	Terminals: Brass
	Earth Strap: Mild Steel
	Terminal Screws: Steel and Yellow Passivated
	Silver "on-lay" copper/brass contacts.
Back Box Depth	25mm – 47mm
Cable Size	4 x 1.5mm ² or 2 x 2.5mm ²
Terminal Size	Live: 3.5mm
	Earth: 3.5mm
Load Rating	10AX (Suitable for Inductive loads)
Modular	Yes
Gang	1
2 Way	Yes
Intermediate	No
Warranty	10 Years Domestic

Standards	BS EN 60669
Additional Information	Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram supplied with the relevant product.
	Bare earth cables must always be covered with appropriate sleeving and
	wired to the earth terminal.
	Interchangeable with switches in the MiniGrid system.

V1.0