

SPECIFICATION SHEET

Product Code

VP*152

Description

2 Gang 2 Way 400W/VA Resistive/ Inductive Dimmer Switch



General Information				
Dimensions	88mm x 88mm x 8mm (Excluding Gaskets)			
Finishes Available	Replace * with: AB (Antique Brass), BN (Black Nickel), BR (Polished Brass), CH (Polished Chrome), PN (Pearl Nickel), SB (Satin Brass), SC (Satin Chrome), and SS (Stainless Steel). (Supplied with Black and White gaskets)			
Material Composition	Front Plate: Stainless Steel Terminals: Brass Earth Strap: Mild Steel Terminal Screws: Steel and Yellow Passivated Silver "on-lay" copper/brass contacts.			
Back Box Depth	35mm – 47mm			
Cable Size	2 x 1.5mm ²			
Resistive	Yes			
Inductive	Yes			
Interchangeable Dimmer Switch Modules	MD9001	MD9010	MD9022	MD9042
	Yes	Yes	Yes	Yes
Type	Leading Edge			
Suitability	Tungsten, Halogen, and Low Voltage May be suitable for use with some dimmable LED light sources. We recommend seeking advice with the lamp/luminaire manufacturer on whether the dimmer has been tested and are compatible with their product.			
Warranty	10 Years Domestic			

Standards	BS EN 60669 BS EN 55015
-----------	----------------------------

Additional Information	We recommend using branded tungsten halogen lamps that incorporate internal fuses. The use of inferior, non-branded lamps may require the nominal rating of the dimmer to be reduced. When dimming low voltage lighting, this dimmer must be used with dimmable, leading edge transformers only. Always check compatibility prior to installation and if in doubt, seek advice with transformer manufacturer. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram supplied with the relevant product. We DO NOT recommend mixing electronic and magnetic transformers on the same dimmer switch. Interchangeable with dimmers in the Mini Grid system 
------------------------	---