

SPECIFICATION SHEET

Product Code CMA171

Description 10AX 1 Gang 2 Way Architrave Switch



General Information	
Dimensions	85mm x 30mm x 9.5mm 56mm between centre fixing holes.
Material composition	Rear Housing: Nylon Front Plate: Urea Terminals: Brass Terminal Screws: Steel and Yellow Passivated Silver "on-lay" copper/brass contacts
Back Box Depth	25mm – 47mm Can only be used with the dedicated architrave back box CMA175 and can only be surface mounted.
Cable Size	4 x 1.5mm ² or 2 x 2.5mm ²
Terminal Size	Live: 3.5mm
Load Rating	10AX (Suitable for Inductive loads)
Modular	Yes
Gang	1
2 Way	Yes
Warranty	20 Years Domestic

Standards	BS EN 60669
-----------	-------------

Additional Information	Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram supplied with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases. All products independently tested achieved a 99.9% kill rate across all four types of the strains of bacteria – MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae. Interchangeable with switches in the Mini Grid system.
------------------------	--

