

MODE

SPECIFICATION SHEET

Product Code

CMA022

Description

20A DP Control Switch With Flex Outlet Bottom





General Information	
Dimensions	86mm x 86mm x 9.5mm
Material composition	Rear Housing: Nylon
	Front Plate: Urea
	Terminals: Brass
	Earth Strap: Mild Steel
	Terminal Screws: Steel and Yellow Passivated
	Silver "on-lay" copper/brass contacts
Back Box Depth	25mm – 47mm
Cable Size	4 x 2.5mm ²
Terminal Size	Live: 5mm
	Neutral: 5mm
	Earth: 5mm
Switched	Yes
Double Pole	Yes
Twin Earth	Yes
Flex Outlet	Yes (Through the Bottom)
Print	No
Warranty	20 Years Domestic

Stallualus BS LIV 00009	Standards	BS EN 60669
-------------------------	-----------	-------------

Additional Information	Ensure that the mains supply is isolated before commencing installation
	and refer to the circuit diagram supplied with the relevant product.
	Bare earth cables must always be covered with appropriate sleeving and
	wired to the earth terminal.
	All white moulded accessories are manufactured using Urea
	Formaldehyde, which has similar inherent properties to antimicrobial
	additives that inhibit the growth of infectious diseases. All products
	independently tested achieved a 99.9% kill rate across all four types of the
	strains of bacteria – MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae
	Flex Outlet Diameter: 10mm

V1.0