


SPECIFICATION SHEET

Product Code CMA013

Description 10AX 3 Gang 2 Way Plate Switch



General Information	
Dimensions	86mm x 86mm x 9.5mm
Material composition	Rear Housing: Nylon Front Plate: Urea Rocker: Urea Terminals: Brass Earth Strap: Mild Steel Terminal Screws: Steel and Yellow Passivated Silver "on-lay" copper/brass contacts
Back Box Depth	16mm – 47mm
Cable Size	4 x 1.5mm ² or 2 x 2.5mm ²
Load Rating	10AX (Suitable for Inductive Loads)
Modular	Yes
Terminal Size	Live: 3.5mm
Gang	3
2 Way	Yes
Intermediate	No
Warranty	20 Years Domestic

Standards	BS EN 60669
-----------	-------------

Additional Information	Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram supplied with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases. All products independently tested achieved a 99.9% kill rate across all four types of the strains of bacteria – MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae. Interchangeable with switches in the Mini Grid system.
------------------------	--

